



DUCTROD RAPID

Designed to push a duct rod into an underground duct.

Tool free installation

When utilizing DuctRod RAPID, the configuration and installation can be deployed without any usage of tools. This makes every job more effective as the machine can quickly be adapted to the specific job saving you time.

Adaptable to various manholes

It is equipped with a flexible clamping unit, allowing you to attach the machine to the sidewall of the manhole securing more stable installation.

Effective rod pushing

Each job is mechanized, which help you improve efficiency and minimizes the risk of costly errors. For rods up to 25 mm.

Adjustable Torque Distance and Speed measurement for complete rod control

SPECIFICATIONS

Item No incl. Power Pack:.....	101-220106002
Rod diameter:.....	9-25 mm
Duct diameter:.....	10-40 mm
Installation speed:.....	Up to 80 m/min
Max. hydraulic pressure.....	110 bar
Pushing/pulling force:	0-200 kg
Clamping unit range:	475-900 mm
Weight:.....	68 kg
Length ¹⁾ :.....	1050 mm
Width:.....	475 mm
Height:.....	790 mm

¹⁾ Without clamping unit

INCLUDED

When purchasing DuctRod RAPID incl. hydraulic power pack

- Control valve for DuctRod RAPID



- 5 m hose



- 25 mm duct holder inserts



- 1 set of chains



FREMCO A/S DENMARK
EMAIL: SALES@FREMCO.DK | TELEPHONE: +45 72 30 12 13 | WWW.FREMCO.DK

VALID FROM APRIL 19, 2022