

SOLAR ACCESS SYSTEM



The Solar Access System provides a safe working platform combined with certified edge protection at roof level. The system comprises one Solar Platform, one Easi-Dec platform and a Catwalk which provides either an 8m or 10m long working area. Additional Decs and Catwalks can be added to provide a limitless modular system.

The Solar Access System also includes 2 rolling window bars, strap operated legs and a purpose designed hoist for lifting solar panels to roof level.

Technical Description

▶ Load rating	600kg uniformly distributed
▶ Lifting capacity	75kg
▶ System weight	258kg
▶ Platform size	1 x 2m x 880mm deep
▶ Hinged opening (1)	1360mm x 217mm wide
▶ Platform Size	1 x 2m x 800mm deep
▶ 4m Catwalk dim.	4.6m x 620mm
▶ Material	H30 (6082T6) aluminium
▶ Standard legs	3.3m - 5.5m platform height

Additional Options

▶ Super legs (2m platform only)	4.5m - 6.8m platform height
▶ 16' legs	3m - 4.75m platform height
▶ 14' legs	2.75m - 4.15m platform height
▶ 9.5" Bungalow legs	2.34m - 2.9m platform height
▶ 6m Catwalk dim.	6.6m x 635mm

Compliance

- ▶ EN13374 Class C
- ▶ EN 12811-1
- ▶ Patent Registration GB24388722

Photographs for illustration purposes only. Ladders not included

