

TECHNICAL SPECIFICATION



Powercap® Infinity® Respirator

Blue / CEA646-000-500



DESCRIPTION

The PowerCap® Infinity® PAPR – a fully integrated TH3 powered air respirator offering four of the highest levels of protection in one intuitive head-mounted unit. Offering 4-in-1 above the neck protection, PowerCap® Infinity® is the perfect choice for many industries where dust poses a danger to health. The unit represents the very latest in Powered Air Purifying Respiratory technology, combining decades of innovation from JSP in the fields of respiratory, head, eye and face protection.

OPTIONS

Black (CEA646-001-100)

Blue (CEA646-000-500)

White (CEA646-000-100)

SAFETY STANDARDS

EN 12941 • EN 397 • EN 166 • ANSI/ISEA Z89.1



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.



























Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 21 Nov 2022 / Copyright 2018 - 2022, JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Impact Resistance 50 Joules		EN 50365 ELECTRICAL INSULATION 1000V
	Lateral Deformation Yes		Molten Metal Yes - Helmet Only
	Maximum Temperature +50°C		Minimum Temperature +5°C
	ABS Shell Yes		Recyclable Shell
	Textile Harness		Depth Adjustment 3D Harness
	Slip Ratchet Wheel		Ventilation No
	Reflective Option Fitted		Integrated Eyewear Optional
	JSPCheck Yes		Optional 4 point chinstrap (EN397 Compliant) Optional
	Classification TH3		Usage P R SL (A Reusable Solid & Liquid Particulate Aerosol Filter)
	Exhalation Valve Twin Exhalation Valve To Reduce CO2 Build-Up		Minimum Filtration Efficiency 99.8%
	Maximum Total Inward Leakage (TIL) 0.2% When Fitted To PowerCap® Infinity® Respirator		Nominal Protection Factor 500
	UK Assigned Protection Factor 40		Mask Design A Turbo Hood Powered Air Purifying Respirator (Loose Fitting)
	Face Seal Type Hypoallergenic Material		Latex free Yes
	Metal Free No		Filter Shelf Life 5 Years
	Filter Material Pleated Media		Battery Type Rechargeable Lithium-ion 3.6v, 5.2Ah, 18.72Wh. Expected Life Of 500 Cycles When Charged, Stored and Used In Accordance With User Instructions
	RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2		LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2
	Manufacturer's Trademark JSP Dagger		Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1
	Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. B		Resistance to Molten Metals and Hot Solids (optional) 9
	BSI Kitemark Yes		Product Weight 1042g
	Noise Level 61.1dB		




JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 21 Nov 2022 / Copyright 2018 - 2022, JSP Limited. All Rights Reserved.






Powerful Twin Turbo Performance

The patented Twin Turbo Technology controls the airflow through the headtop to maximise user comfort and optimise energy efficiency. Real time diagnostics ensure that the twin impeller motor unit delivers the optimum level of airflow depending on the wearer's demands and regulates the intake and internal pressure delivering a minimum of 160 litres a minute of filtered clean air.



No need to FACE FIT test

PowerCap® Infinity® removes the need for fit testing, ensuring that a high volume of clean air is delivered to the breathing zone giving a high level of protection.



TH3 Performance

PowerCap® Infinity® offers respiratory protection to TH3, with a Nominal Protection Factor of 500 (UK APF 40). TH3 is the highest possible rating in the EN12941:1998 + A2:2008 standard.



Smart PPE

Real time diagnostics monitor the system and the wearer twice per second, giving the user accurate, dynamic feedback. Periods of high respiratory demand are monitored and catered for by constantly maintaining a positive pressure inside the respirator. Feedback is given on battery and filter condition via the heads up display and audible notifications.



Head Protection

PowerCap® Infinity® is built around the super strong ABS shell of the EVO®5 Olympus® industrial safety helmet. Fitted with the Revolution® Flex wheel ratchet harness, the helmet is designed to reduce pressure for the perfect fit and all-day comfort.



Panoramic Impact Visor

The optical class 1 visor conforms to EN166.B offering impact protection at speeds of up to 270 mph (tested using a 6mm steel ball bearing). The visor has a replaceable peel-off visor protector to prolong its life.



High Efficiency Filters

The high capacity HEPA filters coupled with the aerodynamically optimised pre-filter covers ensure that PowerCap® Infinity® delivers 160 litres per minute of clean air to the user with maximum battery efficiency. Filters can be effortlessly replaced using an intuitive quick-change bayonet system.




Ear Defenders

The PowerCap® Infinity® has been developed to seamlessly integrate with the optional Sonis® helmet mounted ear defenders. Designed by the JSP R&D team and working with a leading UK acoustic engineering research facility, the Sonis® helmet mounted range peaks at an unbeaten SNR 36dB. The helmet adaptor and the cushion surface area work together to provide optimum cushion pressure and comfort.



Tested to the MAX

Hundreds of hours of human treadmill tests were conducted in a purpose built salt dust challenge chamber to optimise mass, balance and sealing elements. Extensive user trials were conducted, putting the PowerCap® Infinity® to the test in a variety of harsh conditions.



Minimal Maintenance

PowerCap® Infinity® has been developed as a modular system, making it easy to disassemble and reassemble for ease of cleaning and maintenance. To ensure the optimal performance of PowerCap® Infinity® it is important that maintenance is carried out on a regular basis. No specialist tools required.



Perfect Fit to Combat Dust

Dust in the workplace is a significant issue. The latest HSE figures (2017) show that 18,000 new cases of work-related respiratory disease were diagnosed. A significant proportion of these were the result of exposure to silica. While the problem is widely acknowledged and use of respiratory equipment is high, it is often not suitable for the person or the environment it is being used in.



youtu.be/jS1Fr-xVS1I



youtu.be/IMJIVCKiDdo



DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-powercap_infinity.pdf \(PDF\)](#)

