



Product data sheet

Power tools for trade & industry

Cordless Rotary Hammer with SDS plus

GBH 18V-26F



Universal rotary hammer with quick-change chuck in the SDS plus cordless category

The most important data

Impact energy (according to EPTA 05/2016)	2.6 J
Drilling dia. in concrete with hammer drill bits	4 – 26 mm
Impact rate at rated speed	0 – 4,350 bpm

Part Number 0 611 910 000

[> More product information](#)

Technical data

Technical data

Impact energy (according to EPTA 05/2016)	2.6 J
Impact rate at rated speed	0 – 4,350 bpm
Rated speed	0 – 980 rpm
Battery voltage	18.0 V
Tool holder	SDS plus

Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 26 mm
Opt. app. range in concrete with hammer drill bits	8 – 16 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	15.2 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	9.6 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Optional GDE 18V-16 Professional dust extraction unit integrates with the hammer for a self-contained HEPA dust solution
- KickBack Control and Electronic Precision Control for better tool handling and increased user protection
- Delivers 2.6 J of impact energy for fast drilling and high chisel removal performance

