

# FL41

## Optical Fault Locator for Service Activation and Maintenance



The FL41 is a budget friendly and palm-sized Fault Locator/Optical Power Meter for measuring fiber spans from 10 m up to 20 km in length. The FL41f has a built-in filter for in-service fault locating. The FL41 is the perfect tool for service activation technicians who need to measure short fiber links and drop fiber for PON, 5G rollout, FTTx, LAN/WAN, and CATV.



### Key Features

- Singlemode cable length verification
- Single test port - fixed SCAPC connector
- Less than 30 seconds typical test time with one touch automatic mode
- In-Service testing with built-in filter
- NoApp™ QR code generation capability for faster result saving\*
- Simple user interface that saves time on the job
- High contrast display with backlight
- Handheld, lightweight rugged design
- Splash and dust resistant design
- Save up to 10 test results
- Micro USB charging point
- Battery autonomy >350 tests
- Measure in meters or feet

### Key Specifications

#### FL41 Fault Locator with OPM

Optical Fault Locator

- Wavelength: 1625 nm
- Measurement Range: 10 m to 20 km
- Class 1 Laser Safety

OPM

- Wavelength range: 1260 to 1680 nm
- Calibrated wavelengths: 1310, 1490, 1550, and 1625 nm
- Measurement range: -35 to 0 dBm

#### FL41f Fault Locator

- Wavelength: 1625 (F) nm
- Measurement Range: 10 m to 20 km
- In-Service Filter isolation: 50 dB
- Class 1 Laser Safety

\*Patent pending

## Test Results Saving and Transfer

A unique QR code method is used to save and transfer measurements results from the FL41 optical fault locator. Simply scan the QR code and process the test data directly on your mobile device. The NoApp™ feature eliminates the need to download specialized Android or iOS Apps to your mobile device – the QR code embeds all the necessary reporting, commenting, sharing, and uploading.\*



## VeSion® R-Server Workforce/Productivity System

A centralized server application designed for medium-to-large service providers facing the enormous challenge of managing and coordinating hundreds or even thousands of installations per day. The VeSion R-Server collects field test results for billing/record keeping purposes and simplifies inventory management. Used in conjunction with QR code test reporting function, this back-office application reduces customer call-backs and associated truck rolls, maximizing workforce efficiency and lowering operational costs.

### Cloud-Based One System Platform



\*Patent pending

## Optical Specifications

Fault Locator	FL41
Wavelength (nm)	1625 ±10 nm
Filter Isolation (dB) <sup>1</sup>	50
Distance Range (m)	10 m to 20 km
Distance Measurement Accuracy (m) <sup>2</sup>	±(1 + .01 x L)
Dynamic Range (dB)	4
Laser Safety	Class 1 per 60825-1:2014 edition
Power Meter	
Calibrated Wavelengths (nm) <sup>3</sup>	1310/1490/1550/1625
Power range (dBm)	-35 to 0
Power measurement accuracy, (dB) <sup>4</sup>	±1
Display Resolution (dB)	0.1
Optical Connector	Fixed SC/APC connector

### Notes

1. FL41f only.
2. With end reflectance at least -42 dB and refractive index 1.468. For non-reflective ends, distance measurement accuracy is ±2.5%.
3. 1625 nm only on FL41f.
4. At room temperature.

## Ordering Information

Part Number	Description
Z06-99-278P	FL41 Optical Fault Locator, 1625nm(F), 10m to 20 km
Z06-99-279P	FL41 Optical Fault Locator, 1625nm with OPM, 10m to 20 km

## General Specifications

Size:	129 x 61 x 38 mm (H x W x D) 5.1 x 2.4 x 1.5 in.	Connectivity:	Micro USB interface, data transfer via QR code and web application
Weight:	<205 g (<0.45 lbs.) w/OPM option	Display:	>High contrast, 28 x 23 mm LCD, 96 x 80 pixels with backlight
Construction:	Rugged, polycarbonate chassis, 1 meter drop tested	Operating Temp:	-10 °C to +50 °C
Battery:	Two alkaline AA or two rechargeable NiMH, 2150 mAh	Storage Temp:	-20 °C to +70 °C
Power Supply:	Micro USB interface, 5 VDC adapter/charger	Humidity:	0% to 95%, non-condensing



VeEX Inc.  
2827 Lakeview Court  
Fremont, CA 94538 USA  
Tel: +1.510.651.0500  
Fax: +1.510.651.0505  
www.veexinc.com  
customercare@veexinc.com

© 2023 VeEX Inc. All rights reserved.  
VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.  
D05-00-209P B01 2023/06