

**Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

D55 High Strength Retainer Adhesive

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Adhesives, sealants

**Uses advised against**

Any non-intended use.

**1.3. Details of the supplier of the safety data sheet**

Company name: Delta Adhesives Limited  
Place: Units 39-40 Claycliffe Business Park, Barnsley, S75 1JU, United Kingdom  
Telephone: +44 (0)1226 381571  
Internet: [www.delta-adhesives.co.uk](http://www.delta-adhesives.co.uk)  
Responsible Department: sales@delta-adhesives.co.uk

**1.4. Emergency telephone number:** +44 (0)1226 381571 (Mo-Fr, 08:00-16:00)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Indications of danger: C - Corrosive  
R phrases:  
Causes burns.  
May cause sensitisation by skin contact.

**GHS classification**

Hazard categories:  
Skin corrosion/irritation: Skin Corr. 1A  
Serious eye damage/eye irritation: Eye Dam. 1  
Respiratory/skin sensitization: Skin Sens. 1  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazard Statements:  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

**2.2. Label elements****Hazardous components which must be listed on the label**

methacrylic acid, monoester with propane-1,2-diol  
acrylic acid, prop-2-enoic acid  
Aliphatic urethane acrylate

Signal word: Danger  
Pictograms: GHS05-GHS07

**Hazard statements**

H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

**Safety Data Sheet****Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 2 of 12

H335 May cause respiratory irritation.

**Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P501 Dispose of contents/container to in accordance with official regulations.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
248-666-3	methacrylic acid, monoester with propane-1,2-diol	
27813-02-1	Xi - Irritant R36-43	45 - < 50 %
	Eye Irrit. 2, Skin Sens. 1; H319 H317	
201-177-9	acrylic acid, prop-2-enoic acid	5 - < 10 %
79-10-7	C - Corrosive, Xn - Harmful, N - Dangerous for the environment R10-20/21/22-35-50	
607-061-00-8	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Aquatic Acute 1; H226 H332 H312 H302 H314 H400	5 - < 10 %
	Aliphatic urethane acrylate	
-	Xi - Irritant R38-43	
	Skin Irrit. 2, Skin Sens. 1; H315 H317	
201-254-7	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide	< 1 %
80-15-9	O - Oxidizing, T - Toxic, C - Corrosive, Xn - Harmful, N - Dangerous for the environment R7-23-21/22-48/20/22-34-51-53	
617-002-00-8	Org. Perox. E, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, STOT RE 2, Skin Corr. 1B, Aquatic Chronic 2; H242 H331 H312 H302 H373 ** H314 H411	< 1 %
204-055-3	2'-Phenylacetohydrazide	
114-83-0	T - Toxic, Xi - Irritant R25-36/37/38-43	
	Acute Tox. 3, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H301 H319 H335 H315 H317	

Full text of R and H phrases: see Section 16.

**Further Information**

Product does not contain listed SVHC substances.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).

**Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 3 of 12

**After inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**After contact with skin**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Immediately get medical attention.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

**After ingestion**

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. Immediately get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

**6.2. Environmental precautions**

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the assimilated material according to the section on waste disposal.

Clear contaminated area thoroughly.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation.  
Wear suitable protective clothing. ( Refer to chapter 8. )

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Further information on handling**

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.  
General protection and hygiene measures: refer to chapter 8

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

**Advice on storage compatibility**

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Radioactive substances. Infectious substances.

**Further information on storage conditions**

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Protective and hygiene measures**

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove contaminated clothing immediately and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored separately from work clothing. Protect skin by using skin protective cream.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

**Hand protection**

Pull-over gloves of rubber. DIN EN 374

Suitable material:

(Breakthrough time  $\geq$  480 min, penetration time (maximum wearing period): 160 min)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking

**Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 5 of 12

off and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

**Skin protection**

Suitable protection of the body: Protective clothing:

**Respiratory protection**

Respiratory protection required in case of:  
insufficient ventilation.

Generation/formation of aerosols  
Generation/formation of mist  
exceeding critical value

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type : A / P2/P3  
The filter class must be suitable for the maximum contaminant concentration  
(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is  
exceeded, closed-circuit breathing apparatus must be used!

**Environmental exposure controls**

Do not empty into drains or the aquatic environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	Green
Odour:	characteristic

**Test method**

pH-Value:	not determined
-----------	----------------

**Changes in the physical state**

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not determined

**Explosive properties**

none/none

Lower explosion limits:	not determined
Upper explosion limits:	not determined

**Oxidizing properties**

none/none

Vapour pressure:	not determined
Density:	not determined
Viscosity / dynamic:	not determined

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

Stable under normal storage and handling conditions.

**Safety Data Sheet****Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 6 of 12

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

**10.5. Incompatible materials**

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

**10.6. Hazardous decomposition products**Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Acute toxicity**

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
27813-02-1	methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50	>2000 mg/kg	Rat.	ECHA Dossier
	dermal	LD50	>5000 mg/kg	Rabbit.	ECHA Dossier
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	ATE	500 mg/kg		
	dermal	LD50	> 294 mg/kg	Rabbit.	RTECS
	inhalative (4 h) vapour	LC50	>5,1 mg/l	Rat.	ECHA Dossier
	inhalative aerosol	ATE	1,5 mg/l		
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide				
	oral	LD50	382 mg/kg	Rat.	IUCLID
	dermal	LD50	500 mg/kg	Rat.	RTECS
	inhalative (4 h) vapour	LC50	(200) mg/l	Mouse.	IUCLID
	inhalative aerosol	ATE	0,5 mg/l		
114-83-0	2'-Phenylacetohydrazide				
	oral	LD50	270 mg/kg	Mouse.	

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

**Sensitising effects**

May cause an allergic skin reaction. (methacrylic acid, monoester with propane-1,2-diol), (Aliphatic urethane acrylate), (2'-Phenylacetohydrazide)

Respiratory or skin sensitisation:

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

**STOT-single exposure**

May cause respiratory irritation. (2'-Phenylacetohydrazide)

**Severe effects after repeated or prolonged exposure**

**Safety Data Sheet****Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 7 of 12

Based on available data, the classification criteria are not met.

methacrylic acid, monoester with propane-1,2-diol:

Subchronic oral toxicity (90d, Rat.) NOAEL = 300 mg/kg(bw)/day; literature information: ECHA Dossier

acrylic acid, prop-2-enoic acid:

Subchronic oral toxicity (90d, Rat.) NOAEL = 40 mg/kg; literature information: ECHA Dossier

Subchronic inhalative toxicity (90d, Rat.) LOAEC = 0,015 mg/l; literature information: ECHA Dossier

cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide:

Subchronic inhalative toxicity (Rat.) NOAEC = 31 mg/m<sup>3</sup>; literature information: ECHA Dossier

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

methacrylic acid, monoester with propane-1,2-diol:

In-vitro mutagenicity: in vitro mammalian chromosome aberration test = positive. literature information:

Mutation Research 517 (1-2): 187-198

OECD Guideline 471 (Bacterial Reverse Mutation Assay) = negative. literature information: ECHA Dossier

OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay) = negative. literature information: ECHA Dossier

OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) = negative. literature information: ECHA Dossier

In-vivo mutagenicity: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) = negative.

literature information: ECHA Dossier

Carcinogenicity: Rat.) NOAEC = >2,05 mg/l; literature information: ECHA Dossier

Developmental toxicity/teratogenicity (Rat.) NOAEL = 50 mg/kg(bw)/day; literature information: ECHA Dossier

acrylic acid, prop-2-enoic acid:

In-vitro mutagenicity: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) = negative.

literature information: ECHA Dossier

In-vivo mutagenicity: No experimental indications of mutagenicity in-vivo exist. literature information: ECHA Dossier

Carcinogenicity: (Mouse.) NOAEL = >10 mg/kg(bw)/day; literature information: ECHA Dossier

Developmental toxicity/teratogenicity (Rat.) NOAEC = 0,075 mg/l; literature information: ECHA Dossier

cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide:

In-vitro mutagenicity: OECD Guideline 471 (Bacterial Reverse Mutation Assay) = positive. literature information: ECHA Dossier

No experimental indications of mutagenicity in-vivo exist. literature information: ECHA Dossier

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**SECTION 12: Ecological information****12.1. Toxicity**



**Safety Data Sheet****Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
27813-02-1	methacrylic acid, monoester with propane-1,2-diol					
	Acute fish toxicity	LC50	833 mg/l	96 h	Scophthalmus maximus	
	Acute crustacea toxicity	EC50	>143 mg/l	48 h	Daphnia magna	ECHA Dossier
79-10-7	acrylic acid, prop-2-enoic acid					
	Acute fish toxicity	LC50	27 mg/l	96 h	Onchorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	0,13 mg/l	72 h	Desmodesmus subspicatus	MSDS extern
	Acute crustacea toxicity	EC50	95 mg/l	48 h	Daphnia magna	ECHA Dossier
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide					
	Acute fish toxicity	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	3,1 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier
	Acute crustacea toxicity	EC50	18,84 mg/l	48 h	Daphnia magna	ECHA Dossier

**12.2. Persistence and degradability**

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
27813-02-1	methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	>81%	28	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide			
	OECD 301B / ISO 9439 / EWG 92/69 Anhang V, C.4-C	3%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			

**12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
27813-02-1	methacrylic acid, monoester with propane-1,2-diol	0,97
79-10-7	acrylic acid, prop-2-enoic acid	0,35
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide	2,16

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**Further information**

Do not empty into drains or the aquatic environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.



**Safety Data Sheet****Delta D55 High Strength Retainer Adhesive**

Product code: D55

Page 9 of 12

**Waste disposal number of waste from residues/unused products**

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

- 080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.


**Waste disposal number of contaminated packaging**

- 150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances  
Classified as hazardous waste.

**Contaminated packaging**

Handle contaminated packaging in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number:** UN 1760  
**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S.  
(acrylic acid, prop-2-enoic acid; cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8  
  
Classification code: C9  
Special Provisions: 274  
Limited quantity: 1 L  
Transport category: 2  
Hazard No: 80  
Tunnel restriction code: E

**Other applicable information (land transport)**

Excepted quantity: E2

**Inland waterways transport (ADN)**

- 14.1. UN number:** UN 1760  
**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S.  
(acrylic acid, prop-2-enoic acid; cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8

## Delta D55 High Strength Retainer Adhesive

Product code: D55

Page 10 of 12



Classification code: C9  
Special Provisions: 274  
Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number:** UN 1760  
**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S.  
(Acrylic acid; Cumene hydroperoxide)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8



Marine pollutant: NO  
Special Provisions: 274  
Limited quantity: 1 L  
EmS: F-A, S-B

**Other applicable information (marine transport)**

Excepted quantity: E2

**Air transport (ICAO)**

**14.1. UN number:** UN 1760  
**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S.  
(Acrylic acid; Cumene hydroperoxide)  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8



Special Provisions: A3 A803  
Limited quantity Passenger: 0.5 L  
IATA-packing instructions - Passenger: 851  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 855  
IATA-max. quantity - Cargo: 30 L

**Other applicable information (air transport)**

Passenger-LQ: Y840  
Excepted quantity: E2

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

refer to chapter 6-8

## Safety Data Sheet

### Delta D55 High Strength Retainer Adhesive

Product code: D55

Page 11 of 12

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

irrelevant

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

1999/13/EC (VOC): No information available. VOC Directive 2004/42/EC: No information available.

##### Additional information

The preparation is dangerous in the sense of Directive 1999/45/EC.  
This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].  
Not subject to regulation 96/82/EC.  
REACH 1907/2006 Appendix XVII, No 3

##### National regulatory information

Employment restrictions: Observe employment restrictions for young people.  
Water contaminating class (D): 2 - water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

Rev. 1,00, 16.12.2014, Initial release

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level

#### Full text of R phrases referred to under Sections 2 and 3

07	May cause fire.
10	Flammable.
20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
21/22	Harmful in contact with skin and if swallowed.
23	Toxic by inhalation.
25	Toxic if swallowed.
34	Causes burns.
35	Causes severe burns.
36	Irritating to eyes.

## Safety Data Sheet

### Delta D55 High Strength Retainer Adhesive

Product code: D55

Page 12 of 12

36/37/38	Irritating to eyes, respiratory system and skin.
38	Irritating to skin.
43	May cause sensitisation by skin contact.
48/20/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.

#### Full text of H statements referred to under Sections 2 and 3

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*