

LOW DENSITY UNDERGROUND POLYETHYLENE BARRIER TAPE WITH TWO STAINLESS STEEL WIRES APPLIED ON

DIMENSIONS: MM. 150X100 MT.

TECHNICAL DATA SHEET

TECHNICAL NAME	POLYETHYLENE LOW DENSITY
CHIMICLA NAME	OMOPOLYMER POLYETHYLENE
CAS NUMBR	9002-88-4
APPEARANCE	FOIL
DENSITY	910/940 KG. M3
APPARENT DENSITY	500/600 KG. M3
FUSION PAUSE	100-120°C
SPONTANEOUS COMBUSTION	340° C (ISO 871)
TEXTS	INDELEBLE TEXTS, ALKALINE AGENTS RESISTANT, UNDERGROUND ACID RESISTANT
TRANSPARENT MATERIAL	POLYPROPYLENE 30MY
ADESIVE	ACRYLIC
STAINLESS STEEL WIRES	AISI 304 SP. 0.40 MM
TOTAL THICKNESS	130 - 140 MY
WAVELINE WITH ELONGATION	15% (+/- 5%)
DETECTABLE BY	IMPULSES GENERATOR

COMBY ITALIA s.r.l.

Sede Legale: Via Roma, 28
25080 PADENGHE S/G (Brescia)
Sede Operativa: Via delle Pozzette, 13/A
25080 SOIANO DEL LAGO (Brescia)
Tel. 0305 671006 r.a. - Fax 0305 603601
www.combyitalia.it - P.IVA: 01897719982

Pietro Polotti