

C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

1 / 17

In conformity to Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code: C40 Trades code: VC40

UFI: UNG0-ANT9-F802-FGKD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Sectors of use: Industrial Manufacturing[SU3], Private households[SU21], Public domain[SU22] Product category: Adhesives, Sealants

Uses advised against
Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Carima Srl SRL Via dei Brughi 30/31, 20060 Gessate (MI) Italy Tel. 0039.02 95384225 Fax 0039.02 70058164 carima@carima.biz

1.4. Emergency telephone number

CAV Osp. Pediatrico Bambino Gesù Roma Piazza Sant'Onofrio, 4 00165 tel 06 68593726
Az. Osp. Univ. Foggia Foggia V.le Luigi Pinto, 1 71122 tel 0881 732326
Az. Osp. "A. Cardarelli" Napoli Via A. Cardarelli, 9 80131 tel 081 7472870
CAV Policlinico "Umberto I" Roma V.le del Policlinico, 155 00161 tel 06 49978000
CAV Policlinico "A. Gemelli" Roma Largo Agostino Gemelli, 8 00168 tel 06 3054343
Az. Osp. "Careggi" U.O. Tossicologia Medica Firenze Largo Brambilla, 3 50134 tel 055 7947819
CAV Centro Nazionale di Informazione Tossicologica Pavia Via Salvatore Maugeri, 10 27100 tel 0382 24444
Azienda Ospedaliera Papa Giovanni XXII Bergamo Piazza OMS, 1 24127 te 800 883 300
Azienda ospedaliera Universitaria integrata (AOUI) Verona 8000118558
Azienda ospedaliera Niguarda Ca' Grande, piazza Ospedale Maggiore 3, Milano; 02-66101029

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

#2/17

In conformity to Regulation (EU) 2020/878

Pictograms:

GHS07

Hazard Class and Category Code(s): Skin Irrit. 2, Skin Sens. 1, Eye Irrit. 2

Hazard statement Code(s):

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

If brought into contact with eyes, the product causes significant irritations which may last for more than 24 hours, if brought into contact with skin, it causes significant inflammation with erythema, scabs, or edema The product, if brought into contact with skin can cause skin sensitization.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

GHS07 - Warning

Hazard statement Code(s):

H315 - Causes skin irritàtion.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Supplemental Hazard statement Codε (s):

not applicable

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention P261 - Avoid breathing vapours.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. R move contact lenses, if

present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

Disposal

P501 - Dispose of contents/container in accordance to local, regional, national regulations.

2-hydroxyethyl methacrylate 98%

UFI: UNG0-ANT9-F802-FGKD

2.3. Other hazards

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII





C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

#3/17

In conformity to Regulation (EU) 2020/878

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
2-hydroxyethyl methacrylate 98%	>= 20 < 30%	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2, H319 ATE oral = 5.000,0 mg/kg ATE dermal = 5.000,0 mg/kg	ND	868-77-9	212-782-2	01-211949 0169-29-00 00
acrylic acid	>= 0,1 < 1%	Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1A, H314; Acute Tox. 4, H332; Aquatic Acute 1, H400 Limits: STOT SE 3, H335 %C >=1; Acute toxicity M-factor = 1 ATE oral = 1.000,0 mg/kg	607-061-00-8	79-10-7	201-177-9	ND
cumene hydroperoxide	>= 0,1 < 1%	Flam. Liq. 3, H226; Org. Perox. E, H242; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Acute Tox. 3, H335; STOT SE 3, H335; STOT RE 2, H373; Aquatic Chronic 2, H411 Limits: Skin Corr. 1B, H314 %C >=10; Skin Irrit. 2, H315 3<= %C <10; Eye Dam. 1, H318 3<= %C <10; Eye Irrit. 2, H319 1<= %C <3; STOT SE 3, H335 1<= %C <10; Acute toxicity M-factor = 1 Chronic toxicity M-factor = 1 ATE oral = 382,0 mg/kg ATE dermal = 1.100,0	617-002-00-8	80-15-9	201-254-7	ND



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

4 / 17

In conformity to Regulation (EU) 2020/878

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
		mg/kg ATE inhal = 2,0mg/l/4 h				

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product).:

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

Direct contact with eyes (of the pure product).:

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Rinse mouth. Do not induce vomiting. Call a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

In conformity to Regulation (EU) 2020/878

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Wear mask, gloves and protective clothing.

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities. Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

Nothing in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Wear protective gloves/protective clothing/eye protection/face protection.

In residential areas do not use on large surfaces.

At work do not eat or drink.

5 / 17



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

#6/17

In conformity to Regulation (EU) 2020/878

Contaminated work clothing should not be allowed out of the workplace. See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool place, away from sources of heat and `direct exposure of sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Private households:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Public domain:

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

acrylic acid:

TLV: 2 ppm as TWA (skin) A4 (not classifiable as a human carcinogen); (ACGIH 2005).

MAK: 10 ppm 30 mg / m³ Peak limitation category: I (1); Pregnancy risk group: C; (DFG 2005).

- Substance: 2-hydroxyethyl methacrylate 98%

DNEL

Systemic effects Long term Workers inhalation = 4,9 (mg/m3)

Systemic effects Long term Workers dermal = 1,3 (mg/kg bw/day)

PNEC

Sweet water = 0.482 (mg/I)

sediment Sweet water = 3,79 (mg/kg/sediment)

STP = 10 (mg/l)

ground = 0.476 (mg/kg ground)

- Substance: acrylic acid

DNEL

Local effects Long term Workers inhalation = 30 (mg/m3)

Local effects Long term Workers dermal = 1 (mg/kg bw/day)

Local effects Long term Consumers dermal = 1 (mg/kg bw/day)

Local effects Long term Consumers inhalation = 3,6 (mg/m3)

PNEC

Sweet water = 0,003 (mg/l)

sediment Sweet water = 0,0236 (mg/kg/sediment)

Sea water = 0.0003 (mg/l)

sediment Sea water = 0,00236 (mg/kg/sediment)

intermittent emissions = 0,0013 (mg/l)

STP = 0.9 (mg/l)

ground = 1 (mg/kg ground)



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

#7/17

In conformity to Regulation (EU) 2020/878

 Substance: cumene hydroperoxide **DNEL** Systemic effects Long term Workers inhalation = 6 (mg/m3) **PNEC** Sweet water = 0.0031 (mg/l)sediment Sweet water = 0,023 (mg/kg/sediment) Sea water = $0.00031 \, (mg/l)$ sediment Sea water = 0,0023 (mg/kg/sediment) intermittent emissions = 0,031 (mg/l) STP = 0.35 (mg/l)ground = 0.0029 (mg/kg ground)

8.2. Exposure controls



Private households: No specific monitoring foreseen

Public domain:

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

When handling the pure product use safety glasses (spectacles cage) (EN 166).

- (b) Skin protection
- (i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

When handling the pure product wear full protective skin clothing.

- (c) Respiratory protection Not needed for normal use.
- (d) Thermal hazards No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties











C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

#8/17

In conformity to Regulation (EU) 2020/878

Physical and chemical properties	Value	Determination method
Physical state	Liquid	
	Liquid	
Colour	Blue	
Odour	Characteristic	
pH	irrelevant	
Melting point/freezing point	not determined	
Evaporation rate	irrelevant	
Flammability	nonflammable	
Boiling point or initial boiling point and boiling range	irrelevant	
Partition coefficient n-octanol/water (log value)	irrelevant	
Auto-ignition temperature	irrelevant	
Odour threshold	irrelevant	
Decomposition temperature	irrelevant	
Density and/or relative density	1,05 g/ml	
Solubility(ies)	Organic Solvent	
Water solubility	not soluble	
Lower and upper explosion limit	not explosive	
Relative vapour density	not determined	
Vapour pressure	not determined	
Kinematic viscosity	2.000 - 4.000 mPa.s	

9.2. Other information

9.2.1 Information with regard to physical hazard classes

- a) Explosives
- i) sensitivity to shock Irrilevant
- ii) effect of heating under confinement Irrilevant
- iii) effect of ignition under confinement Irrilevant
- iv) sensitivity to impact Irrilevant
- v) sensitivity to friction Irrilevant
- vi) thermal stability Irrilevant



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

9 / 17

In conformity to Regulation (EU) 2020/878

- vii) package Irrilevant
- b) Flammable gases
- i) Tci / explosion limits Irrilevant
- ii) fundamental burning velocity Irrilevant
- c) Aerosols Irrilevant
- d) Oxidising gases Irrilevant
- e) Gases under pressure Irrilevant
- f) Flammable liquids Irrilevant
- g) Flammable solids
- i) burning rate, or burning time as regards metal powders Irrilevant
- ii) statement on whether the wetted zone has been passed Irrilevant
- h) Self-reactive substances and mixtures
- i) decomposition temperature Irrilevant
- ii) detonation properties Irrilevant
- iii) deflagration properties Irrilevant
- iv) effect of heating under confinement Irrilevant
- v) explosive power, if applicable Irrilevant
- i) Pyrophoric liquids Irrilevant
- j) Pyrophoric solids
- statement on whether spontaneous ignition occurs when poured or within five minutes thereafter, as regards solids in powder form Irrilevant
- ii) statement on whether pyrophoric properties could change over time Irrilevant



ISTANT C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

10 / 17

In conformity to Regulation (EU) 2020/878

- k) Self-heating substances and mixtures
- i) statement on whether spontaneous ignition occurs and the maximum temperature rise obtained Irrilevant
- ii) results of screening tests referred to in section 2.11.4.2 of Annex I to Regulation (EC) No 1272/2008, if relevant and available Irrilevant
- I) Substances and mixtures, which emit f lammable gases in contact with water. The following information may be provided
- i) identity of the emitted gas, if known Irrilevant
- ii) statement on whether the emitted gas ignites spontaneously Irrilevant
- iii) gas evolution rate Irrilevant
- m) Oxidising liquids Irrilevant
- n) Oxidizing solids Irrilevant
- o) Organic peroxides
- i) decomposition temperature Irrilevant
- ii) detonation properties Irrilevant
- iii) deflagration properties Irrilevant
- iv) effect of heating under confinement Irrilevant
- v) explosive power Irrilevant
- p) Corrosive to metals
- metals that are corroded by the substance or mixture Irrilevant
- ii) corrosion rate and statement on whether it refers to steel or aluminium Irrilevant
- iii) reference to other sections of the safety data sheet with regard to compatible or incompatible materials Irrilevant
- q) Desensitised explosives
- i) desensitising agent used



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

11 / 17

In conformity to Regulation (EU) 2020/878

Irrilevant

- ii) exothermic decomposition energy Irrilevant
- iii) corrected burning rate (Ac) Irrilevant
- iv) explosive properties of the desensitised explosive in that state Irrilevant

9.2.2 Other safety characteristics

- a) mechanical sensitivity Irrilevant
- b) self-accelerating polymerisation temperature Irrilevant
- c) formation of explosible dust/air mixtures Irrilevant
- d) acid/alkaline reserve Irrilevant
- e) evaporation rate Irrilevant
- f) miscibility Irrilevant
- g) conductivity Irrilevant
- h) corrosiveness Irrilevant
- i) gas group Irrilevant
- j) redox potential Irrilevant
- k) radical formation potential Irrilevant
- I) photocatalytic properties Irrilevant

SECTION 10. Stability and reactivity



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

In conformity to Regulation (EU) 2020/878

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Nothing to report

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides. It can ignite in contact with oxidants mineral acids, strong oxidants agents, strong reducing agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATE(mix) oral = 34.019,1 mg/kg

ATE(mix) dermal = 64.327,5 mg/kg

ATE(mix) inhal = 215.3 mg/l/4 h

(a) acute toxicity: cumene hydroperoxide: 594/5000

The substance is corrosive to the eyes, the skin and the respiratory tract. Corrosive by ingestion. Inhalation of this substance may cause pulmonary edema (see Notes). The effects can be delayed. Medical observation is indicated. ACUTE RISKS / SYMPTOMS

INHALATION Sore throat. Burning sensation. Cough. Respiratory difficulty. Shortness of breath. Symptoms may occur late (see Notes).

CUTE Redness. Ache. Skin burns.

EYES Redness. Ache. Serious deep burns.

INGESTION Burning sensation. Abdominal pain. Shock or collapse.

- (b) skincorrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.
- (c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

2-hydroxyethyl methacrylate 98%: Serious eye damage / eye irritation

rabbit, Draize, (own analysis), irritating

Irritating to eyes Category 2B (UN-GHS)

(d) respiratoryorskinsensitisation: The product, if brought into contact with skin can cause skin sensitization.

2-hydroxyethyl methacrylate 98%: Respiratory or skin sensitization

12 / 17



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

13 / 17

In conformity to Regulation (EU) 2020/878

guinea pig, GPMT - Sensitizer

Skin sensitization Category 1B (UN-GHS)

- (e) germ cell mutagenicity: based on available data, the classification criteria are not met
- (f) carcinogenicity: based on available data, the classification criteria are not met
- (g) eproductivetoxicity: based on available data, the classification criteria are not met
- (h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met
- (i) specific target organ toxicity (STOT) repeated exposure2-hydroxyethyl methacrylate 98%: Repeated Toxicity administration

rat, oral, 7th Sept., OECD 422 - NOAEL - 100 mg / kg

cumene hydroperoxide: Species: Rat

NOAEL: 0.031 mg/l

Application method: inhalation (dust / mist / fumes)

Exposure time: 90 d

(j) aspiration hazard: based on available data, the classification criteria are not met

LD50 (rat) Oral (mg/kg body weight) = 65789

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 144736

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 394,7

Related to contained substances:

2-hydroxyethyl methacrylate 98%:

Toxicokinetics, metabolism and distribution

The substance is rapidly metabolized

General indications

Contact with the eyes and skin should be avoided, as well as the breathing of the product vapors.

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 5000

acrylic acid:

LD50 (rat) Oral (mg/kg body weight) = 1000

cumene hydroperoxide:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation, through the skin and by ingestion.

INHALATION RISK: No indication can be given about the rate in which a harmful concentration in the air is reached on evaporation of this substance at 20 $^{\circ}$ C.

N O T E The symptoms of pulmonary edema often do not occur within a few hours and are exacerbated by physical exertion. Rest and medical observation are therefore essential. Immediate administration of an appropriate inhalation therapy by a physician or personnel authorized by him should be considered.

LD50 (rat) Oral (mg/kg body weight) = 382

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 1100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 2,01

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

acrylic acid:

CL50 Oncorhynchus mykiss (rainbow trout): 27 mg / l; 96 h



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

14 / 17

In conformity to Regulation (EU) 2020/878

Guideline 203 for the OECD Test

Toxicity to daphnia and other aquatic invertebrates

EC5 E.sulcatum: 20 mg / l; 72 h

(toxic concentration limit) (Lit.)

EC50 Daphnia magna (Water flea): 47 mg / l; 48 h

(IUCLID)

Toxicity to algae OECD TG 201 IC50 Desmodesr

IC50 Desmodesmus subspicatus (green algae): 0,13 mg / I; 72 h

(IUCLID)

Toxicity to bacteria

EC5 Pseudomonas putida: 41 mg / l; 16 h (toxic concentration limit) (IUCLID) EC20 activated sludge: 900 mg / l; 30 min

ISO 8192 (IUCLID).

NOEC (mg/I) = 0.2

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

12.6. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

12.7. Other adverse effects

No adverse effects



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

15 / 17

In conformity to Regulation (EU) 2020/878

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies. Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number or ID number

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

14.2. UN proper shipping name

None

14.3. Transport hazard class(es)

None

14.4. Packing group

None

14.5. Environmental hazards

None

14.6. Special precautions for user

No data available.

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EU) No 1357/2014 - waste: HP4 - Irritant — skin irritation and eye damage HP13 - Sensitising

Substances in the Candidate List (REACH Article 59)



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

16 / 17

In conformity to Regulation (EU) 2020/878

Based on available data, no SVHC substances are present

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information

16.1. Other information

Description of the hazard statements exposed to point 3

H315 = Causes skin irritation.

H317 = May cause an allergic skin reaction.

H319 = Causes serious eye irritation.

H226 = Flammable liquid and vapour.

H302 = Harmful if swallowed.

H312 = Harmful in contact with skin.

H314 = Causes severe skin burns and eye damage.

H332 = Harmful if inhaled.

H400 = Very toxic to aquatic life.

H242 = Heating may cause a fire.

H331 = Toxic if inhaled.

H335 = May cause respiratory irritation.

H373 = May cause damage to organs through prolonged or repeated exposure.

H411 = Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

Causes skin irritation. Classification procedure: Calculation method

May cause an allergic skin reaction. H317 Classification procedure: Calculation method

H319 Causes serious eye irritation. Classification procedure: Calculation method

GENERAL BIBLIOGRAPHY:

- Council Regulation (EC) 1907/2006 of the European Parliament (REACH)

- Regulation (EC) 1272/2008 of the European Parliament (CLP) and subsequent updates
- Council Regulation (EC) no 758/2013 of the European Parliament
- Regulation (EC) no 2020/878 of the European Parliament
- Regulation (EC) No 528/2012 European Parliament and subsequent updates
- Commission Regulation (EC) No 790/2009 of 10 August 2009 Commission Regulation (EU) No 286/2011 of 10 March 2011
- Commission Regulation (EU) No 618/2012 of 10 July 2012
- Commission Regulation (EU) No 487/2013 of 8 May 2013
- Council Regulation (EU) No 517/2013 of 13 May 2013
- Commission Regulation (EU) No 758/2013 of 7 August 2013
- Commission Regulation (EU) No 944/2013 of 2 October 2013
- Commission Regulation (EU) No 605/2014 of 5 June 2014
- Commission Regulation (EU) 2015/491 of 23 March 2015
- Commission Regulation (EU) No 1297/2014 of 5 December 2014- Council Regulation (EC) 648/2004 of the European Parliament and subsequent updates
- The Merck Index
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique
- Patty-Industrial Hygiene and Toxicology



C40

Issued on 01/31/2019 - Rel. # 1 on 11/30/2022

17 / 17

In conformity to Regulation (EU) 2020/878

- N.I. Sax-Dangerous properties of Industrial Materials-7 Ed., 1989

Note to the user:

the information in this tab are based on knowledge available to us on the date of the latest version.

The user must ensure the fitness and completeness of the information in relation to the specific use of the product. You should not interpret it as a guarantee of any specific property of the product.

For the use of the product does not fall under our direct control, the obligation of the user to observe under their own liability laws and regulations on hygiene and safety. Do not assume liability for improper use.

This tab replaces and cancels all previous