




**Ementelle UK Ltd.**  
Haughhead  
Hawick TD9 8LF  
United Kingdom

info@ementelle.com  
ementelle.com

## Product Datasheet MHT 1564

### Blown Fibre Generic Specification DBmf Bundles (12/8)




#### Product Description

Assemblies of strong 12/8 polyethylene (PE) microducts (m/d), each with low friction performance. These m/ds will accept all blown fibre products that can be installed into the more traditional 10/8 m/ds. The 4-way has a 5/3.5 m/d in the centre. The 5-way has a strong 8/3.5 m/d in the centre. Each assembly (bundle) is surrounded by a thin flexible PE sheath. These strong metal-free bundles are designed for direct burial in suitably prepared ground. They can normally be used to create a fibre 'drop' link to a building. The narrow bundles may also be used in slot-cut deployments (eg 15mm slot).

#### Product Benefits



Microducts are tested according to IEC 60794-5



Blowing track: up to 2000m, route and fibre/cable dependent



Em-Liner for Low Friction and best blowing results




UV-Protection up to 2 years in EU



Pressure tight up to 15 bar

#### Application and Design




#### Inner surface:

Smooth or ribbed + Em-Liner

#### Colour identification of single ducts:

Translucent with stripes or uni coloured possible



#### Other colours upon request

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Ementelle can take no responsibility for actions taken based on the information contained in this document. Ementelle reserves the right to make changes to this document without notice. All sales of product are subject to Ementelle's terms and conditions of sale only, which can be found on Ementelle's website. This document is protected by copyright (c) Ementelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Ementelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers. [www.ementelle.com](http://www.ementelle.com)

**Generic Details: Single Microduct**

Material	Polyethylene HDPE	
Outer diameter	12.0mm	8.0mm**
Inner diameter	8.0mm	3.5mm
Mass, nominal	60g/m	38g/m
Min. bending radius of primary duct*	120mm	80mm
Max. pull tension, single duct	400N (40 kg)	250N (25 kg)
Crush load at 10 % compression approx.	1600 N (160 kg)	1300 N (130 kg)
Max. Blowing pressure	15 bar	

\*This radius relates to the microduct capability only and does not indicate a good radius for blowing FU.

\*\*8/3.5 is the centre m/d in the 5-way

1. These m/ds are compatible with designated 12 mm push-fit connectors.
2. Max air pressure for blowing: 15 bar.
3. Storage of unprotected primary microducts: Indoors and well shielded from daylight.

**Generic Details: Microduct Bundle**

Material	Polyethylene HDPE
Wall thickness	1.0 mm
Number single ducts	2-12 (+8 mm central duct)

**Product-Specific Details**

Type	Outer Diameter	Mass	Max. Pull Tension (Installation)	Min. Bend Radius
<b>12/8mm</b>				
2-WAY DBMF	14,0 x 26,0 mm	184 g/m	0,90 kN / 90 kg	220 mm
3-WAY DBMF	14,0 x 38,0 mm	267 g/m	1,4 kN / 140 kg	220 mm
4-WAY DBMF	31,0 mm	353 g/m	1,8 kN / 180 kg	440 mm
5-WAY DBMF	34,4 mm	435 g/m	2,4 kN / 240 kg	600 mm
6-WAY DBMF	38,0 mm	466 g/m	2,6 kN / 260 kg	600 mm
7-WAY DBMF	38,0 mm	531 g/m	2,8 kN / 280 kg	650 mm
12-WAY DBMF	51,0 mm	862 g/m	4,8 kN / 480 kg	700 mm

\*After applying pulling tensions, allow time for the pulled product to relax. See Installation manual.

Note 1: Diameters and thicknesses are measured to the nearest 0.1mm.

Note 2: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 3: Sketches are for information purposes only, and should not be used for inspection.

Note 4: When interpreting performance data and installing tubes, bundles, or fibre units, it is assumed that the user has been trained by Emtelle.

Note 5: All data is believed to be accurate

Note 6: Users must establish the suitability of these products for their own applications.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers. [www.emtelle.com](http://www.emtelle.com)

**Operating Parameters**

Installation temperature	-20°C...+40°C
Transportation and storage temperature	-40°C...+60°C
Installation + Blowing ideal	+5°C...+20°C

**Testing**

Crush	IEC 60794-1-2-Method E3	Procedure to IEC 60794-5
Impact	IEC 60794-1-2-Method E4	Procedure to IEC 60794-5
Flexibility	IEC 60794-1-2-Method E11	Procedure to IEC 60794-5
Repeated Bend	IEC 60794-1-2-Method E6	Procedure to IEC 60794-5
Kink	IEC 60794-1-2-Method E10	Procedure to IEC 60794-5

**Additional Information**

- Emtelle FibreFlow Microducts are compatible with Emtelle 12mm connectors, end caps and gas stops
- Emtelle's Microducts and bundles often exceed IEC60794-5 requirements. If you require precise or higher test results, please contact us for more information
- Bundles on drums are covered with UV-protection foil to ensure 1 year UV-protection plus
- Optionally, the bundles can be supplied with a 0.63mm locating wire (copper, coating 88Ω / km)
- Optionally, the bundles can be manufactured with a thick-walled bundle 2.2mm for higher tensile force and additional protection
- Production with PP sheath possible
- Stripes on the sheath possible
- Customer specific print available
- The sheath can be opened using a suitable sheath removal tool (see installation manual)

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers. [www.emtelle.com](http://www.emtelle.com)