

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

Non-Latching In-Line RCD Safety Unit

Product Images

Product Code: P85-3176



The Masterplug Safety in-line RCD continuously monitors the power supply to an electrical appliance and cuts off the power within 40 milliseconds if an earth current fault is detected. This is fast enough to prevent a fatal electrical shock.

Specifically designed for heavy duty applications, the water resistant casing of the unit is rated at IP65 when used with plugs, sockets and connectors of an equivalent rating. The RCD is a non-latching type so when power to the RCD is disconnected, due to a power cut or switching off the mains, the RCD will trip & have to be re-set when power returns.

- Cuts power if the power to an appliance is turned off
- Added protection against fatal electric shocks
- Maximum load 3120W, 240VAC
- 30mA Trip speed, 40ms (typical)

Description

The Masterplug Safety in-line RCD continuously monitors the power supply to an electrical appliance and cuts off the power within 40 milliseconds if an earth current fault is detected. This is fast enough to prevent a fatal electrical shock.

Specifically designed for heavy duty applications, the water resistant casing of the unit is rated at IP65 when used with plugs, sockets and connectors of an equivalent rating. The RCD is a non-latching type so when power to the RCD is disconnected, due to a power cut or switching off the mains, the RCD will trip & have to be re-set when power returns.

- Cuts power if the power to an appliance is turned off
- Added protection against fatal electric shocks
- Maximum load 3120W, 240VAC
- 30mA Trip speed, 40ms (typical)