

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Drummond MTL20PD-S Test Lamp and Proving Device

Product Images Product Code: C70-2097





Short Description

This handy bundle contains a Drummond MTL20 test lamp and a PD440 440V proving device in a

combination carry case. The proving device can be used to verify the functioning of the test lamp.

Set comprises:

C70-2015 Martindale PD440S 440V AC Proving Unit

Safe electrical working requires the use of a voltage indicator that has been proven with a suitable proving device before and after use to ensure the instrument is working correctly in accordance with the Electricity at Work Regulations.

The Martindale PD440S is a direct replacement for the industry standard PD440. Its voltage output is matched to the VI13800, the MTL10 and MTL20 Drummond test lamps and all other 440V voltage indicators and testers.

In addition to all the benefits of the industry standard Martindale PD440 unit, the S models feature a tough overmoulded low profile case and come with an MG3 magnetic hanger (excluding kits). They are fast and easy to use, instantly supplying the test voltage for both high and low impedance voltage indicators, test lamps and meters.

C70-7361 Drummond MTL20 Test Lamp

The MTL20 incorporates two test buttons, one on the body of the unit and one on the probe. Simultaneous depression of both buttons enables the unit to draw a high current, allowing the user to differentiate between phantom voltages and hazardous persistent voltages.

The robust design meets the recommendations of the Health and Safety Executive in their guidance notes on the electrician's test lamp (GS38) as well as complying with BS EN 61243-3 and BS EN 61010, CAT III 1000V and CAT IV 600V.

A unique feature of this new Drummond test lamp are the four distinctive bands of illumination, with a 360° viewing angle, providing indication of voltages above 50, 100, 200 & 400 volts, even in bright sunlight. This allows for accurate identification of potentially lethal voltages at 50V and enables the user to distinguish between 110V, 230V and phase to phase voltages in a 3 phase system.

Both the lamp housing and the probe have a finger shield and insulated probe tip with only 4mm of exposed metal. A two layer double insulated cable with white inner insulation gives a clear warning of abrasion that might compromise the user's safety, and is resistant against heat and oil. To enable use in most circumstances, a right angled probe tip is supplied in addition to the two straight tips. For maximum ease of use the right angled probes can be rotated through 90, 180 and 270 degrees

C70-7365 Martindale TC69 VIPD Soft Carry Case

A soft carry case for the Martindale voltage tester and the proving device. Never be without the right proving device for your voltage indicator. The clear front pocket allows the proving unit to be used without having to remove it from the case. A handy neck strap is included. Also available as part of a VTPD safe isolation kit including voltage tester, proving unit and carry case.

For further details, please see the individual product specifications.

Description

This handy bundle contains a Drummond MTL20 test lamp and a PD440 440V proving device in a combination carry case. The proving device can be used to verify the functioning of the test lamp.

Set comprises:

C70-2015 Martindale PD440S 440V AC Proving Unit

Safe electrical working requires the use of a voltage indicator that has been proven with a suitable proving device before and after use to ensure the instrument is working correctly in accordance with the Electricity at Work Regulations.

The Martindale PD440S is a direct replacement for the industry standard PD440. Its voltage output is matched to the VI13800, the MTL10 and MTL20 Drummond test lamps and all other 440V voltage indicators and testers.

In addition to all the benefits of the industry standard Martindale PD440 unit, the S models feature a tough overmoulded low profile case and come with an MG3 magnetic hanger (excluding kits). They are fast and easy to use, instantly supplying the test voltage for both high and low impedance voltage indicators, test lamps and meters.

C70-7361 Drummond MTL20 Test Lamp

The MTL20 incorporates two test buttons, one on the body of the unit and one on the probe. Simultaneous depression of both buttons enables the unit to draw a high current, allowing the user to differentiate between phantom voltages and hazardous persistent voltages.

The robust design meets the recommendations of the Health and Safety Executive in their guidance notes on the electrician's test lamp (GS38) as well as complying with BS EN 61243-3 and BS EN 61010, CAT III 1000V and CAT IV 600V.

A unique feature of this new Drummond test lamp are the four distinctive bands of illumination, with a 360° viewing angle, providing indication of voltages above 50, 100, 200 & 400 volts, even in bright sunlight. This allows for accurate identification of potentially lethal voltages at 50V and enables the user to distinguish between 110V, 230V and phase to phase voltages in a 3 phase system.

Both the lamp housing and the probe have a finger shield and insulated probe tip with only 4mm of exposed metal. A two layer double insulated cable with white inner insulation gives a clear warning of abrasion that might compromise the user's safety, and is resistant against heat and oil. To enable use in most circumstances, a right angled probe tip is supplied in addition to the two straight tips. For maximum ease of use the right angled probes can be rotated through 90, 180 and 270 degrees

A soft carry case for the Martindale voltage tester and the proving device. Never be without the right proving device for your voltage indicator. The clear front pocket allows the proving unit to be used without having to remove it from the case. A handy neck strap is included. Also available as part of a VTPD safe isolation kit including voltage tester, proving unit and carry case.

Dimensions 265mm x 100mm x 100mm

For further details, please see the individual product specifications.