

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

SMD LED Tripod Site Light 20W 1800 Lm 110v

Product Images Product Code: P40-3538







Short Description

The SMD LED Sitelight has been designed for commercial use, and features the latest LED lighting

technology. Its single LED provides a high light output of 1800 lumens with the added advantage of a low power consumption and a cool running temperature that avoids the burn hazards commonly associated with halogen lighting.

SMD LEDs are maintenance free and more resilient to impact damage that can cause conventional halogen tubes to fail if a light is hit or knocked over. The lamp head is manufactured from die-cast aluminium and is IP65 rated for water and dust ingress protection. The lamp head is fully adjustable and mounted on a sturdy telescopic tripod, two twist grip locks enable the tripod height to be quickly adjusted between 910 and 1810mm.

LED power: 20 watt Lumen output: 1,800 Beam angle: 120° Colour range: 6500K LED type: SMD

Lens material: Impact resistant glass

Cable Length: 2.5M

Adjustable Height: 910-1810mm

Voltage: 110v

IP rating: IP65

Description

The SMD LED Sitelight has been designed for commercial use, and features the latest LED lighting technology. Its single LED provides a high light output of 1800 lumens with the added advantage of a low power consumption and a cool running temperature that avoids the burn hazards commonly associated with halogen lighting.

SMD LEDs are maintenance free and more resilient to impact damage that can cause conventional halogen tubes to fail if a light is hit or knocked over. The lamp head is manufactured from die-cast aluminium and is IP65 rated for water and dust ingress protection. The lamp head is fully adjustable and mounted on a sturdy telescopic tripod, two twist grip locks enable the tripod height to be quickly adjusted between 910 and 1810mm.

LED power: 20 watt Lumen output: 1,800 Beam angle: 120° Colour range: 6500K LED type: SMD

IP rating: IP65

Lens material: Impact resistant glass

Cable Length: 2.5M

Adjustable Height: 910-1810mm

Voltage: 110v