

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU


Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

T-Matting Trench Cover MK3

Product Images Product Code: S00-3563









Short Description

T-Matting is a new and unique innovation, designed specifically for 'Narrow' and 'Micro' trenching applications - which is becoming a popular method for the installation of fibre broadband networks and has been tried and tested by many of the major network providers. Supplied in 2 metre lengths.

- Footways can remain open so it provides minimal disruption to the public.
- Protects against water ingress, depressions and shrinkage further down the line.
- Highly visible for additional public safety.
- Tested to BS7976 slip test.
- Tested to the Load Test outlined in the HAUC advice note 2018/01. *However, this is not a bridging device and should always be used with support of ground.

Product Features

- 240mm wide with a 90mm x 20mm T-Piece.
- Prevents interference when backfilling the trench with foam concrete.
- Developed in conjunction with major network providers for 'narrow trenching' applications.
- New anti-skid technology
- Flexible enough to follow the undulations of the pavement
- Made from 100% recyclable material
- Tested to BS7976 slip test.
- T Matting to be used as temporary cover once trench is backfilled and awaiting reinstatement.
- Made in the UK.

Description

T-Matting is a new and unique innovation, designed specifically for 'Narrow' and 'Micro' trenching applications - which is becoming a popular method for the installation of fibre broadband networks and has been tried and tested by many of the major network providers. Supplied in 2 metre lengths.

Key Benefits of T-Matting:

- Footways can remain open so it provides minimal disruption to the public.
- Protects against water ingress, depressions and shrinkage further down the line.
- Highly visible for additional public safety.
- Tested to BS7976 slip test.
- Tested to the Load Test outlined in the HAUC advice note 2018/01. *However, this is not a bridging device and should always be used with support of ground.

Product Features

- 240mm wide with a 90mm x 20mm T-Piece.
- Prevents interference when backfilling the trench with foam concrete.
- Developed in conjunction with major network providers for 'narrow trenching' applications.
- New anti-skid technology
- Flexible enough to follow the undulations of the pavement
- Made from 100% recyclable material
- Tested to BS7976 slip test.
- T Matting to be used as temporary cover once trench is backfilled and awaiting reinstatement.
- Made in the UK.