
Bosch GBH4-32DFR SDS Plus Multidrill 240V

Product Images

Product Code: P09-9660



Short Description

Robustness combined with durability and excellent performance in the SDS plus category

900 W motor delivers 4.2 J of impact energy for very fast chisel removal rates

Durable due to robust metal gearbox housing design

Vibration Control for effortless and continuous work in time-intensive applications

The powerful GBH 4-32 DFR Professional with SDS plus delivers 4.2 J of impact energy with an 900 W motor for a very fast chisel removal rate. The rotary hammer is designed for durability, featuring a very robust metal gearbox housing. Its Vibration Control enables effortless and continuous work in time intensive applications.

This rotary hammer is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments.

The GBH 4-32 DFR Professional also features a keyless and quick-change chuck, Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock.

Technical Data

Rated input power 900 W

Impact energy 4.2 J

Impact rate at rated speed 0 – 3,600 bpm

Rated speed 0 – 800 rpm

Weight 4.7 kg

Tool holder SDS plus

Packaging dimensions (width x length x height) 353 x 473 x 125 mm

Voltage, electrical 240 V

Drilling range

Drilling dia. concrete, hammer drill bits, from 6 mm

Drilling dia. concrete, hammer drill bits, up to 32 mm

Drilling dia. concrete, hammer drill bits 6 – 32 mm

Opt. appl. range concrete, hammer drill bits 14 – 25 mm

Max. drilling diameter masonry, core cutters 90 mm

Max. drilling diameter in metal 13 mm

Max. drilling diameter in wood 32 mm

Description

Robustness combined with durability and excellent performance in the SDS plus category

900 W motor delivers 4.2 J of impact energy for very fast chisel removal rates

2

Durable due to robust metal gearbox housing design

Vibration Control for effortless and continuous work in time-intensive applications

The powerful GBH 4-32 DFR Professional with SDS plus delivers 4.2 J of impact energy with an 900 W motor for a very fast chisel removal rate. The rotary hammer is designed for durability, featuring a very robust metal gearbox housing. Its Vibration Control enables effortless and continuous work in time intensive applications.

This rotary hammer is intended for drilling and chiselling in concrete, masonry, wood, and metal. It is compatible with various dust attachments.

The GBH 4-32 DFR Professional also features a keyless and quick-change chuck, Reverse Mode, Rotation Control Clutch, Variable Speed, and Vario-Lock.

Technical Data

Rated input power 900 W

Impact energy 4.2 J

Impact rate at rated speed 0 – 3,600 bpm

Rated speed 0 – 800 rpm

Weight 4.7 kg

Tool holder SDS plus

Packaging dimensions (width x length x height) 353 x 473 x 125 mm

Voltage, electrical 240 V

Drilling range

Drilling dia. concrete, hammer drill bits, from 6 mm

Drilling dia. concrete, hammer drill bits, up to 32 mm

Drilling dia. concrete, hammer drill bits 6 – 32 mm

Opt. appl. range concrete, hammer drill bits 14 – 25 mm

Max. drilling diameter masonry, core cutters 90 mm

Max. drilling diameter in metal 13 mm

Max. drilling diameter in wood 32 mm