

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Robin-Amprobe KMP7021 Digital RCD Tester with Ramp Test 230v

Product Images Product Code: C72-3809



Short Description

The Robin-Amprobe RCD tester is a simple to use device, designed to check for correct operation of RCD devices. Features Ramp Test for complete range of testing applications. A residual-current device (RCD) disconnects a circuit whenever the electric current is not balanced between the energised and the neutral conductors. The imbalance indicates that there is a leakage current outside of the system sometimes caused by the person accidentally touching the energized part of the circuit, and sometimes by lack of sufficient insulation (excessive moisture or worn out, poor quality insulation materials).

- Three levels of trip currents (X1/2, X1, X5) for complete range of testing applications
- Ramp test
- 3-LED Proper connection indicator
- Phase switch selection 0° & 180° for positive and negative semi-cycle testing
- Large display
- Designed to allow testing to BS7671 IEE 17th Edition regulations
- Safety CAT III 300V

Contents

Contents: Tester. 3-Wires mains test cord, test lead set with leads/probes/crocodile clips, users manual, strap & carrying case

Description

The Robin-Amprobe RCD tester is a simple to use device, designed to check for correct operation of RCD devices. Features Ramp Test for complete range of testing applications. A residual-current device (RCD) disconnects a circuit whenever the electric current is not balanced between the energised and the neutral conductors. The imbalance indicates that there is a leakage current outside of the system sometimes caused by the person accidentally touching the energized part of the circuit, and sometimes by lack of sufficient insulation (excessive moisture or worn out, poor quality insulation materials).

- Three levels of trip currents (X1/2, X1, X5) for complete range of testing applications
- Ramp test
- 3-LED Proper connection indicator
- Phase switch selection 0° & 180° for positive and negative semi-cycle testing
- Large display
- Designed to allow testing to BS7671 IEE 17th Edition regulations
- Safety CAT III 300V

Contents

Contents: Tester. 3-Wires mains test cord, test lead set with leads/probes/crocodile clips, users manual, strap & carrying case