
STIHL TS410 Concrete Cut Off Saw 300mm

Product Images

Product Code: P57-3843



Short Description

Compact and robust 3.2-kW cut-off machine (300mm/12" cutting wheel) featuring:

Long-life filter system with cyclone pre-separation makes on site maintenance unnecessary.

Extremely low vibration levels (3.9m/s²).

High performance engine with stratified charge system.

Compact design and optimised balance for excellent cutting and guide characteristics.

ElastoStart, primer pump and decompression valve.

Bayonet filler cap for tool free opening.

Can be hand held or used with the FW 20 cart. Supplied with abrasive cutting wheel.

Reduced-emission engine technology

2-stroke engine with stratified charge. A fuel-free layer of air is created between the burned charge in the combustion chamber and the fresh charge in the crankcase, reducing the amount of fuel lost during the charge cycle. This results in more power with a lower weight, up to 20% lower fuel consumption than regular 2-stroke engines and significantly reduced exhaust emissions.

Manual fuel pump (Purger)

A small fuel pump delivers fuel to the carburettor at the touch of a button. This reduces the number of starting strokes required following extended breaks in operations.

Pre-separation air filtration system

STIHL long-life air filtration systems with pre-separation achieve perceptibly longer filter life compared with conventional filter systems. Air drawn in is swirled. The larger, heavier particles are ejected. The pre-cleaned air is routed to the air filter via the pre-separator duct.

Anti-vibration system

Intense vibration at the handles of power tools can lead to long-term effects on blood vessels in the hands and arms. STIHL has therefore developed an effective anti-vibration system whereby the oscillations from the machine's engine are dampened which significantly reduces vibrations at the handles.

Ergonomic grip position

The modern, ergonomic design allows each user to work with an optimal grip position. The loop handle facilitates excellent cutting comfort in any working position.

Semi automatic drive belt tensioning

Light, consistent re-tensioning increases the service life of the belts and shaft bearings.

Specifications

CO2 g/kWh 747
Capacity cm³ 66.7
Performance kW 3.2
Vibration value, right m/s² 1) 3.9
Weight 2) 9.60
Sound pressure level dB(A) 3) 98
Sound power level dB(A) 3) 109
Vibration value, left m/s² 1) 3.9
Tank volume l 0.71
Power output kW/bhp 3.2/4.4
Weight kg 4) 9.4
Sound pressure level dB(A) 5) 98.0
Sound power level dB(A) 5) 109.0
Vibration levels left/right m/s² 6) 3.9/3.9
Cutting wheel mm/in 300 / 12
EPA Certified fuel consumption l/h 2.048

Description

Compact and robust 3.2-kW cut-off machine (300mm/12" cutting wheel) featuring:

Long-life filter system with cyclone pre-separation makes on site maintenance unnecessary.

Extremely low vibration levels (3.9m/s²).

High performance engine with stratified charge system.

Compact design and optimised balance for excellent cutting and guide characteristics.

ElastoStart, primer pump and decompression valve.

Bayonet filler cap for tool free opening.

Can be hand held or used with the FW 20 cart. Supplied with abrasive cutting wheel.

Reduced-emission engine technology

2-stroke engine with stratified charge. A fuel-free layer of air is created between the burned charge in the combustion chamber and the fresh charge in the crankcase, reducing the amount of fuel lost during

the charge cycle. This results in more power with a lower weight, up to 20% lower fuel consumption than regular 2-stroke engines and significantly reduced exhaust emissions.

Manual fuel pump (Purger)

A small fuel pump delivers fuel to the carburettor at the touch of a button. This reduces the number of starting strokes required following extended breaks in operations.

Pre-separation air filtration system

STIHL long-life air filtration systems with pre-separation achieve perceptibly longer filter life compared with conventional filter systems. Air drawn in is swirled. The larger, heavier particles are ejected. The pre-cleaned air is routed to the air filter via the pre-separator duct.

Anti-vibration system

Intense vibration at the handles of power tools can lead to long-term effects on blood vessels in the hands and arms. STIHL has therefore developed an effective anti-vibration system whereby the oscillations from the machine's engine are dampened which significantly reduces vibrations at the handles.

Ergonomic grip position

The modern, ergonomic design allows each user to work with an optimal grip position. The loop handle facilitates excellent cutting comfort in any working position.

Semi automatic drive belt tensioning

Light, consistent re-tensioning increases the service life of the belts and shaft bearings.

Specifications

CO₂ g/kWh 747

Capacity cm³ 66.7

Performance kW 3.2

Vibration value, right m/s² 1) 3.9

Weight 2) 9.60

Sound pressure level dB(A) 3) 98

Sound power level dB(A) 3) 109

Vibration value, left m/s² 1) 3.9

Tank volume l 0.71

Power output kW/bhp 3.2/4.4

Weight kg 4) 9.4

Sound pressure level dB(A) 5) 98.0

Sound power level dB(A) 5) 109.0

Vibration levels left/right m/s² 6) 3.9/3.9

Cutting wheel mm/in 300 / 12

EPA Certified fuel consumption l/h 2.048