

Hypocut F Drop Clamp for EZ AXS & ROC Flat Cables Pk10

Product Images

Product Code: S83-4436



Short Description

The PIA approved Hypocut F drop clamp has been specifically developed to meet the requirements of FTTP network roll-outs in the UK. This cable clamp enables the anchoring of flat aerial drop cables up to 70 metres.

Developed in partnership with Commscope, the Hypocut F drop clamp has the particularity of cutting fibre optic flat cables and especially the Commscope® EZ AXS drop cables in case of excess load. It is also compatible with Corning® ROC Drop cables.

The Hypocut F cable clamp consists of a stainless steel body, a shim with an embedded blade and a plastic wedge equipped with an integrated opening bail.

For flat cables: 6x3mm

Cutting load limit: > 1200N

Material: UV resistant thermoplastic wedge and bail / Stainless steel body and shim

Supplied in a pack of 10

Description

The PIA approved Hypocut F drop clamp has been specifically developed to meet the requirements of FTTP network roll-outs in the UK. This cable clamp enables the anchoring of flat aerial drop cables up to 70 metres.

Developed in partnership with Commscope, the Hypocut F drop clamp has the particularity of cutting fibre optic flat cables and especially the Commscope® EZ AXS drop cables in case of excess load. It is also compatible with Corning® ROC Drop cables.

The Hypocut F cable clamp consists of a stainless steel body, a shim with an embedded blade and a plastic wedge equipped with an integrated opening bail.

For flat cables: 6x3mm

Cutting load limit: > 1200N

Material: UV resistant thermoplastic wedge and bail / Stainless steel body and shim

Supplied in a pack of 10