
Microduct Connector End Cap 18mm Pk10

Product Images

Product Code: Q69-4326



Short Description

18mm push-fit end cap for blown fibre microduct systems.

High impact

Tamper proof lock clip.

Clear body (identify if a cable is installed)

Meets / exceeds the performance criteria of EN 50411-2-8.

The results are based on the testing being performed at 22°C.

Working Pressures and Temperatures:

Blowing pressure (max) 16Bar

Minimum maximum working temperature: -20°C to +50°C

Materials:

Body: Transparent PA

Cartridge: Black POM

Collet: Black POM

Support Ring Orange POM

Seals: NBR suitable for gas

Lock Claw Stainless Steel

Supplied in a pack of 10

Description

18mm push-fit end cap for blown fibre microduct systems.

High impact

Tamper proof lock clip.

Clear body (identify if a cable is installed)

Meets / exceeds the performance criteria of EN 50411-2-8.

The results are based on the testing being performed at 22°C.

Working Pressures and Temperatures:

Blowing pressure (max) 16Bar

Minimum maximum working temperature: -20°C to +50°C

Materials:

Body: Transparent PA

Cartridge: Black POM

Collet: Black POM

Support Ring Orange POM

Seals: NBR suitable for gas
Lock Claw Stainless Steel

Supplied in a pack of 10