



Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge
UB8 2GU

Contact us on:
Tel: 020 8833 2626
Fax: 020 8833 2600
Email: sales@millsltd.com

Company No. 00282704
VAT No. 227082574

12FU G657A2 SM Blown Fibre

2000m

Product Images

Product Code: 90765/2KM



Short Description

12FU G657A2 Singlemode Blown Fibre set in an encapsulating layer providing excellent dimensional and thermal stability.

An outer thermoplastic layer provides a high level of protection and excellent installation properties.

The

FU is designed for blowing into microducts and tube bundles.

The fibres are dry, not coated with gel, thus permitting fast and contamination –free connections.

The FU contain various single mode fibres meeting the ITU-T recommendation G.657 (A1, A2, B2 or B3)

Outer Diameter (Nominal): 1.6mm

Mass (Nominal): 2.2 g/m

Min Bend Radius: 80mm

Fibre Type: Singlemode compliant with G657 (ITU-T) and MHT 2050

Temperatures

Storage: -20°C to +70°C

Installation: -10°C to +50°C

Lifetime: -20°C to +60°C

Attenuation at 20°C (dB/km)

.40 dB/km max at 1310nm to 1625nm

0.30 dB/km max at 1550nm

0.34 dB/km max at 1383nm waterpeak

PMDQ (M= 20, Q=0.01%): $\leq 0.2 \text{ ps} / (\text{km})^{0.5}$

Length 2000 metres (2 Kilometres)

Description

12FU G657A2 Singlemode Blown Fibre set in an encapsulating layer providing excellent dimensional and thermal stability.

An outer thermoplastic layer provides a high level of protection and excellent installation properties.

The

FU is designed for blowing into microducts and tube bundles.

The fibres are dry, not coated with gel, thus permitting fast and contamination –free connections.

The FU contain various single mode fibres meeting the ITU-T recommendation G.657 (A1, A2, B2 or B3)

Outer Diameter (Nominal): 1.6mm

Mass (Nominal): 2.2 g/m

Min Bend Radius: 80mm

Fibre Type: Singlemode compliant with G657 (ITU-T) and MHT 2050

Temperatures

Storage: -20°C to +70°C

Installation: -10°C to +50°C

Lifetime: -20°C to +60°C

Attenuation at 20°C (dB/km)

.40 dB/km max at 1310nm to 1625nm

0.30 dB/km max at 1550nm

0.34 dB/km max at 1383nm waterpeak

PMDQ (M= 20, Q=0.01%): $\leq 0.2 \text{ ps} / (\text{km})^{0.5}$

Length 2000 metres (2 Kilometres)