


# 24FU G657A1 SM Blown Fibre

## 2000m

Product Images

Product Code: 91077/2KM



## Short Description

---

24FU G657A1 SM Blown Fibre designed for installation into microducts.

### Overview

Product Diameter 2.05mm

Product Weight 3.1g/m

Colour Yellow

Metal Free Yes

Minimum Bend Radius (Note 4) 146D

Maximum Installation Tension 95N @ 0.4% Fibre Strain

Product Specification CP3602

Fibre Specification ITU-T G.657.A1, MHT2050

### Fibre Type

24x SM G657A1 Optical Fibres - Blue, orange, green, red, grey, yellow, brown, violet, black, aqua, pink, white, blue, orange, green, red, grey, yellow, brown, violet, black, aqua, pink, white  
Fibres 13 onwards ring marked

### Construction

Outer Sheath PE low friction, yellow, 0.13mm thick

Encapsulation Acrylate resin

Print Marking

Metre mark, 24FU, G657A1, Emtelle, CP3602, batch No, Time/Date,

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction.

## Description

---

24FU G657A1 SM Blown Fibre designed for installation into microducts.

### Overview

Product Diameter 2.05mm

Product Weight 3.1g/m

Colour Yellow

Metal Free Yes

Minimum Bend Radius (Note 4) 146D

Maximum Installation Tension 95N @ 0.4% Fibre Strain

Product Specification CP3602

Fibre Specification ITU-T G.657.A1, MHT2050

#### Fibre Type

24x SM G657A1 Optical Fibres - Blue, orange, green, red, grey, yellow, brown, violet, black, aqua, pink, white, blue, orange, green, red, grey, yellow, brown, violet, black, aqua, pink, white  
Fibres 13 onwards ring marked

#### Construction

Outer Sheath PE low friction, yellow, 0.13mm thick

Encapsulation Acrylate resin

Print Marking

Metre mark, 24FU, G657A1, Emtelle, CP3602, batch No, Time/Date,

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction.