


# 2FU G657A1 SM Blown Fibre 2000m

Product Images

Product Code: 9506/2KM



## Short Description

---

2FU G657A1 singlemode blown fibre designed for installation into microducts.

### Overview

Product Diameter 1.12mm

Product Weight 0.9g/m

Colour Yellow

Metal Free Yes

Minimum Bend Radius (Note 4) 44D

Maximum Installation Tension 16N @ 0.4% Fibre Strain

Product Specification MHT2050/MHT2185

Fibre Specification ITU-T G.657.A1, MHT2050

### Fibre Type One

2x SM G657A1 Optical Fibres - blue, orange

### Fibre Type Two

2x Mechanical Optical Fibres - natural, natural

### Construction

Outer Sheath PE low friction, yellow, 0.03mm thick

Encapsulation Acrylate resin

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction

## Description

---

2FU G657A1 singlemode blown fibre designed for installation into microducts.

### Overview

Product Diameter 1.12mm

2

<https://www.millsltd.com/default/2fu-g657a1-sm-blown-fibre-2000m.html>

09/04/2024

Product Weight 0.9g/m  
Colour Yellow  
Metal Free Yes  
Minimum Bend Radius (Note 4) 44D  
Maximum Installation Tension 16N @ 0.4% Fibre Strain  
Product Specification MHT2050/MHT2185  
Fibre Specification ITU-T G.657.A1, MHT2050

#### Fibre Type One

2x SM G657A1 Optical Fibres - blue, orange

#### Fibre Type Two

2x Mechanical Optical Fibres - natural, natural

#### Construction

Outer Sheath PE low friction, yellow, 0.03mm thick  
Encapsulation Acrylate resin

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction