

2FU G657A1 SM Blown Fibre

2000m

Product Images

Product Code: 9506/2KM



Short Description

2FU G657A1 singlemode blown fibre designed for installation into microducts.

Overview

Product Diameter 1.12mm

Product Weight 0.9g/m

Colour Yellow

Metal Free Yes

Minimum Bend Radius (Note 4) 44D

Maximum Installation Tension 16N @ 0.4% Fibre Strain

Product Specification MHT2050/MHT2185

Fibre Specification ITU-T G.657.A1, MHT2050

Fibre Type One

2x SM G657A1 Optical Fibres - blue, orange

Fibre Type Two

2x Mechanical Optical Fibres - natural, natural

Construction

Outer Sheath PE low friction, yellow, 0.03mm thick

Encapsulation Acrylate resin

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction

Description

2FU G657A1 singlemode blown fibre designed for installation into microducts.

Overview

Product Diameter 1.12mm

2

<https://www.millsLtd.com/default/2fu-g657a1-sm-blown-fibre-2000m.html>

29/04/2024

Product Weight 0.9g/m
Colour Yellow
Metal Free Yes
Minimum Bend Radius (Note 4) 44D
Maximum Installation Tension 16N @ 0.4% Fibre Strain
Product Specification MHT2050/MHT2185
Fibre Specification ITU-T G.657.A1, MHT2050

Fibre Type One

2x SM G657A1 Optical Fibres - blue, orange

Fibre Type Two

2x Mechanical Optical Fibres - natural, natural

Construction

Outer Sheath PE low friction, yellow, 0.03mm thick
Encapsulation Acrylate resin

Length 2000m

Note 1: Diameters and thicknesses are measured to nearest 0.1mm.

Note 2: All dimensions and weight are 'nominal'.

Note 3: 'nominal' data is based on middle-spec, and is for information only, not for inspection purposes.

Note 4: 'D' is the appropriate product diameter for the bending direction