

Prysmian Riser Box 4 Tray

Product Images

Product Code: XCPSC01159



Short Description

The Riser Box Multi Tray (RBMT) is designed for use within apartment blocks and mid/high rise office blocks. The unit houses either 8 splice trays, or 4 splice trays and a module storage area. Each splice tray is able to accommodate 8 fibre splices.

An in-line cable entry port enables the box to be installed onto an in-line riser cable and up to 24 drop ports are available for drop cables of up to 5mm in diameter.

The inner tray module can be moved from left to right enabling the riser cable to be installed into the box on either the left or right hand side.

Features

- Allows splicing from in line or butt cables to customer drop cables.
- Suitable for two butt or one inline cable of up to 15mm in diameter.
- In line cables can enter/exit from the unit on the left or right hand side.
- 24 drop cables (OD 5 mm) or 32 drop cables (OD 4.2 mm) can be spliced. Drop cables exit the unit from the bottom face.
- The drop cable entries are suitable for cables or tubes from 2.5 to 5 mm in diameter.
- Available in two sizes – RBMT4 with 4 trays and a module storage section, or RBMT8 with 8 trays.
- Up to 8 fusion splices or 4 mechanical splices can be accommodated into each of the splice trays (total of 64 fusion or 32 mechanical splices for the RBMT8 and 32 fusion or 16 mechanical splices for the RBMT4).
- Can accommodate optical splitters. Contact Prysmian for further details.
- It's possible to re-launch a cable (OD up to 15 mm) from the bottom face.
- The Storage Area can accept up to 25m of 0.9mm fibre modules.
- Cable management ensures a 20mm minimum bend radius.
- Easily installed and fitted to the wall or inside a riser. Suitable for internal use only and manufactured from UL94-V0 rated material.
- Input and output cables are retained using cable ties.

Description

The Riser Box Multi Tray (RBMT) is designed for use within apartment blocks and mid/high rise office blocks. The unit houses either 8 splice trays, or 4 splice trays and a module storage area. Each splice tray is able to accommodate 8 fibre splices.

An in-line cable entry port enables the box to be installed onto an in-line riser cable and up to 24 drop ports are available for drop cables of up to 5mm in diameter.

The inner tray module can be moved from left to right enabling the riser cable to be installed into the box on either the left or right hand side.

Features

- Allows splicing from in line or butt cables to customer drop cables.
- Suitable for two butt or one inline cable of up to 15mm in diameter.
- In line cables can enter/exit from the unit on the left or right hand side.
- 24 drop cables (OD 5 mm) or 32 drop cables (OD 4.2 mm) can be spliced. Drop cables exit the unit from the bottom face.
- The drop cable entries are suitable for cables or tubes from 2.5 to 5 mm in diameter.
- Available in two sizes – RBMT4 with 4 trays and a module storage section, or RBMT8 with 8 trays.
- Up to 8 fusion splices or 4 mechanical splices can be accommodated into each of the splice trays (total of 64 fusion or 32 mechanical splices for the RBMT8 and 32 fusion or 16 mechanical splices for the RBMT4).
- Can accommodate optical splitters. Contact Prysmian for further details.
- It's possible to re-launch a cable (OD up to 15 mm) from the bottom face.
- The Storage Area can accept up to 25m of 0.9mm fibre modules.
- Cable management ensures a 20mm minimum bend radius.
- Easily installed and fitted to the wall or inside a riser. Suitable for internal use only and manufactured from UL94-V0 rated material.
- Input and output cables are retained using cable ties.