


EZ-Path RFG2 Fire Stop Grommet - Pack of 10

Product Images

Product Code: R02-5107



Short Description

EZ-Path ® Firestop Grommets are a molded, two-piece grommet with an integral fire and smoke sealing

foam membrane for sealing small cable penetrations through framed wall assemblies. Grommet snaps together around cable and locks tightly into the wall.

EZ-Path® Firestop Grommets are tested to meet the exacting criteria of ASTM E814 (UL1479) and CAN/ULC S115. Tested systems provide up to 2 hr fire ratings for small cable penetrations in gypsum board/stud wall assemblies.

Features

- One or more cables with total O.D. up to 0.53" (14 mm) for RFG2
- Easy firestop and smoke seal for a small cable penetrations through fire-rated walls
- For use in gypsum board wall (i.e. drywall) construction• Tested to ASTM E814/UL1479 and CAN/ULC-S115
- Rated for use in Plenums

Specifications

For small cables penetrating gypsum board/stud wall assemblies, the firestop shall consist of a molded, two-piece grommet having a foam fire and smoke sealing membrane that conforms to the outside diameter of the individual cable. The grommet product shall be capable of locking into place to secure the cable penetration within the wall assembly. The grommet shall be UL Classified and tested to the requirements of ASTM E814 (UL1479) and CAN/ULC S115.

Leakage Rating Less Than 1 CFM (ANSI/UL1479)

In-Service Temperature <130° F (54° C)

Overall Length: 1-5/8" (41.3 mm)

Installed Depth (from wall surface): 1-9/16" (39.7 mm)

Required Opening: 1" (25 mm)

Weight: 0.03 lbs (14 g)

Supplied in a pack of 10.

Description

EZ-Path ® Firestop Grommets are a molded, two-piece grommet with an integral fire and smoke sealing foam membrane for sealing small cable penetrations through framed wall assemblies. Grommet snaps together around cable and locks tightly into the wall.

EZ-Path® Firestop Grommets are tested to meet the exacting criteria of ASTM E814 (UL1479) and CAN/ULC S115. Tested systems provide up to 2 hr fire ratings for small cable penetrations in gypsum board/stud wall assemblies.

Features

- One or more cables with total O.D. up to 0.53" (14 mm) for RFG2
- Easy firestop and smoke seal for a small cable penetrations through fire-rated walls
- For use in gypsum board wall (i.e. drywall) construction• Tested to ASTM E814/UL1479 and CAN/ULC-S115
- Rated for use in Plenums

Specifications

For small cables penetrating gypsum board/stud wall assemblies, the firestop shall consist of a molded, two-piece grommet having a foam fire and smoke sealing membrane that conforms to the outside diameter of the individual cable. The grommet product shall be capable of locking into place to secure the cable penetration within the wall assembly. The grommet shall be UL Classified and tested to the requirements of ASTM E814 (UL1479) and CAN/ULC S115.

Leakage Rating Less Than 1 CFM (ANSI/UL1479)

In-Service Temperature <130° F (54° C)

Overall Length: 1-5/8" (41.3 mm)

Installed Depth (from wall surface): 1-9/16" (39.7 mm)

Required Opening: 1" (25 mm)

Weight: 0.03 lbs (14 g)

Supplied in a pack of 10.