

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

## **Tempo Security and Alarm Tracing Kit**

**Product Images Product Code: C00-5055** 



## **Short Description**

Traces Security and Alarm wiring for easy identification

- 2. The choice of industry professionals
- 3. Quickly confirms switch function
- 4. Locates intermittent faults

This toner is designed specification for the Security and Alarm industry, the Model 620 offers convenience, ease of use, and true performance.

As a Continuity tester, the 620 can be connected to a normally open or normally closed loop pair and provides a distinct audible tone when the alarm-condition occurs.

The Latching feature provides a simple method for identifying intermittent failures and confirming operation of switches at remote locations. In the latching mode the model 620 will latch the alarm condition and continue sounding until the tester is reset.

As a tone generator, the unit provides a traditional variable tone that can be applied using the 24" test leads or the RJ11 connector.

A convenient magnetic plate allows the Model 620 to be mounted directly to the control panel cabinet or door.

MF PART NO. 50605072

## **Description**

- 5. Traces Security and Alarm wiring for easy identification
- 6. The choice of industry professionals
- 7. Quickly confirms switch function
- 8. Locates intermittent faults

This toner is designed specification for the Security and Alarm industry, the Model 620 offers convenience, ease of use, and true performance.

As a Continuity tester, the 620 can be connected to a normally open or normally closed loop pair and provides a distinct audible tone when the alarm-condition occurs.

The Latching feature provides a simple method for identifying intermittent failures and confirming operation of switches at remote locations. In the latching mode the model 620 will latch the alarm condition and continue sounding until the tester is reset.

As a tone generator, the unit provides a traditional variable tone that can be applied using the 24" test leads or the RJ11 connector.

A convenient magnetic plate allows the Model 620 to be mounted directly to the control panel cabinet or door.

MF PART NO. 50605072