

GS38 Fused Multimeter Test Lead Set 1.2m

Product Images

Product Code: C46-1075



Short Description

GS38 Safety Probes featuring:

GS 38 Compliant 1.2 Metre Double Skin Silicone Cable. Bi-coloured layers.
1.0mm² c.s.a. 3.6mm Ø Nom.o/d Multistranded very flexible copper core.
Temp. Rating -10°C to +150°C
Fuse Rating: 500mA/1000V/50kA

IEC 61010 Rating.
Measurement Category.
1000V CAT III/600V CAT IV
Current Rating. As Per Fuse
Insulation Category. Double/Reinforced.
Pollution Degree. Two (2)

Designed, manufactured and tested to and are therefore fully compliant to: IEC61010-031:2002
As per IEC requirements.

The product also meet the requirements of the Low Voltage Directive and where applicable complies with HSE GS.38.

Description

GS38 Safety Probes featuring:

GS 38 Compliant 1.2 Metre Double Skin Silicone Cable. Bi-coloured layers.
1.0mm² c.s.a. 3.6mm Ø Nom.o/d Multistranded very flexible copper core.
Temp. Rating -10°C to +150°C
Fuse Rating: 500mA/1000V/50kA

IEC 61010 Rating.
Measurement Category.
1000V CAT III/600V CAT IV
Current Rating. As Per Fuse
Insulation Category. Double/Reinforced.
Pollution Degree. Two (2)

Designed, manufactured and tested to and are therefore fully compliant to: IEC61010-031:2002
As per IEC requirements.

The product also meet the requirements of the Low Voltage Directive and where applicable complies with HSE GS.38.

Ref: 027548