

# Linian SuperClip White 18-20mm Pk25

**Product Images**

**Product Code: R02-1417**



## Short Description

---

Linian SuperClips™ are designed specifically for conduit, armoured (SWA) and grouped cables. The cable clips are suitable for all substrates and provide a robust fixing designed to enable significant rotational stress and to support an impressive tensile load of 44kg.

With SuperClips, the installer can anchor SWA safely and form a bend in the cable without having to remove the clip to do so. SuperClips provide a neat, easy and versatile substitute for plastic cleats and metal saddle clips and eradicate the need for screws, plugs and plastic. SuperClips™ are designed to provide a lasting fix, however, if a design change is required, the clips can be simply removed with a set of pincers.

Available in Colours: Red/Black/**White**/Cream/Purple/Yellow/Orange/Galvanised/Copper

To suit cable diameter: 12-14mm/15-18mm/**18-20mm**/20-22mm/23-25mm

Recommended spacing: 300mm

Hole Diameter\* 10mm

Hole depth: 40mm

Supports a max tensile load of 44kg

18th Edition Compliant

Fire-resistant >1000°C

\*Varies for best fixing according to the substrate

Supplied in a pack of 25

## Description

---

Linian SuperClips™ are designed specifically for conduit, armoured (SWA) and grouped cables. The cable clips are suitable for all substrates and provide a robust fixing designed to enable significant rotational stress and to support an impressive tensile load of 44kg.

With SuperClips, the installer can anchor SWA safely and form a bend in the cable without having to remove the clip to do so. SuperClips provide a neat, easy and versatile substitute for plastic cleats and metal saddle clips and eradicate the need for screws, plugs and plastic. SuperClips™ are designed to provide a lasting fix, however, if a design change is required, the clips can be simply removed with a set of pincers.

Available in Colours: Red/Black/**White**/Cream/Purple/Yellow/Orange/Galvanised/Copper

To suit cable diameter: 12-14mm/15-18mm/**18-20mm**/20-22mm/23-25mm

Recommended spacing: 300mm

Hole Diameter\* 10mm

Hole depth: 40mm

Supports a max tensile load of 44kg

18th Edition Compliant  
Fire-resistant >1000°C

\*Varies for best fixing according to the substrate

Supplied in a pack of 25