

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

## Linian FireClip Red Double 6-8mm Pk100

**Product Images** 

Product Code: R02-1405



Equip yourself with an extraordinary upgrade in fire cable clip design that delivers major benefits in efficiency, safety and value for money.

Perfected through years of development, this exceptional innovation looks simple – and it is. The fire rated cable fixings are expertly designed to save time, money and lives, this remarkable evolution of a vital building component can help you make every job neater and more effective than ever.

Round cables and PVC Trunking For single and double cables Anchor fixings for wire etc Corrosion Resistant – UV Stable 18th Edition Compliant Fire-resistant >1000°C

Available Colours: Red/Black/White as standard For Cream/Purple/Yellow/Orange/Galvanised/Copper & specialist colours – MoQ's & lead times may apply.

Range to suit cable diameters from 4mm – 11mm Recommended spacing: 300mm Hole Diameter\* 6mm Hole depth: 30mm Supports a max tensile load of 24kg.

\*Varies for best fixing according to the substrate.

Supplied in a pack of 100

## Description

Equip yourself with an extraordinary upgrade in fire cable clip design that delivers major benefits in efficiency, safety and value for money.

Perfected through years of development, this exceptional innovation looks simple – and it is. The fire rated cable fixings are expertly designed to save time, money and lives, this remarkable evolution of a vital building component can help you make every job neater and more effective than ever.

Round cables and PVC Trunking For single and double cables Anchor fixings for wire etc Corrosion Resistant – UV Stable 18th Edition Compliant Fire-resistant >1000°C Available Colours: Red/Black/White as standard For Cream/Purple/Yellow/Orange/Galvanised/Copper & specialist colours – MoQ's & lead times may apply.

Range to suit cable diameters from 4mm – 11mm Recommended spacing: 300mm Hole Diameter\* 6mm Hole depth: 30mm Supports a max tensile load of 24kg.

\*Varies for best fixing according to the substrate.

Supplied in a pack of 100

3