

---

# Linian FireClip Black Single 4-6mm Pk100

Product Images

Product Code: R02-1400

---



## Short Description

---

Equip yourself with an extraordinary upgrade in fire cable clip design that delivers major benefits in efficiency, safety and value for money.

Perfected through years of development, this exceptional innovation looks simple – and it is. The fire rated cable fixings are expertly designed to save time, money and lives, this remarkable evolution of a vital building component can help you make every job neater and more effective than ever.

Round cables and PVC Trunking

For single and double cables

Anchor fixings for wire etc

Corrosion Resistant – UV Stable

18th Edition Compliant

Fire-resistant >1000°C

Available Colours: Red/Black/White as standard For Cream/Purple/Yellow/Orange/Galvanised/Copper & specialist colours – MoQ's & lead times may apply.

Range to suit cable diameters from 4mm – 11mm

Recommended spacing: 300mm

Hole Diameter\* 6mm

Hole depth: 30mm

Supports a max tensile load of 24kg.

\*Varies for best fixing according to the substrate.

Supplied in a pack of 100

## Description

---

Equip yourself with an extraordinary upgrade in fire cable clip design that delivers major benefits in efficiency, safety and value for money.

Perfected through years of development, this exceptional innovation looks simple – and it is. The fire rated cable fixings are expertly designed to save time, money and lives, this remarkable evolution of a vital building component can help you make every job neater and more effective than ever.

Round cables and PVC Trunking

For single and double cables

Anchor fixings for wire etc

Corrosion Resistant – UV Stable

18th Edition Compliant

Fire-resistant >1000°C

Available Colours: Red/Black/White as standard For Cream/Purple/Yellow/Orange/Galvanised/Copper & specialist colours – MoQ's & lead times may apply.

Range to suit cable diameters from 4mm – 11mm

Recommended spacing: 300mm

Hole Diameter\* 6mm

Hole depth: 30mm

Supports a max tensile load of 24kg.

\*Varies for best fixing according to the substrate.

Supplied in a pack of 100