

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

# LastMile VRK Armadillo Fibre Blowing Compressor

#### **Product Images**

Product Code: S00-3791



## **Short Description**

The Lastmile VRK20 is a portable compressor designed for cable blowing. With safety and efficiency in

mind, it is designed to meet the requirements for cable blowing installations.

#### <u>Features</u>

- Built in aftercooler
- Automatic optimum air flow delivery the unit will automatically adjust the air flow to optimum volume, this reduces stress on the engine and improves fuel efficiency
- Max operating pressure 15bar / 218psi
- Working Pressure 13Bar / 188psi
- Free air delivery 1000L/min / 35cfm
- Minimum working pressure 5.5bar / 80psi
- Drive system engine-air end, belt drive XP2 over dimensioned
- Compressor cooling system Air/Oil
- Oil cooling capacity 5 litres / 1.33 gallons
- Air outlet temperature 20C + Ambient temperature
- Hose Diameter 3/4"
- Outlet connector Claw
- Noise level EECno 2000/14 <98 LWA
- Battery 12Vcc 300A-30Ah (EN)
- Fuel tank capacity 15L / 4 gallons
- Weight 240K

#### Please see the specification sheet for further details

## Description

The Lastmile VRK20 is a portable compressor designed for cable blowing. With safety and efficiency in mind, it is designed to meet the requirements for cable blowing installations.

#### <u>Features</u>

Built in aftercooler Automatic optimum air flow delivery - the unit will automatically adjust the air flow to optimum volume, this reduces stress on the engine and improves fuel efficiency Max operating pressure 15bar / 218psi Working Pressure 13Bar / 188psi Free air delivery 1000L/min / 35cfm Minimum working pressure 5.5bar / 80psi Drive system engine-air end, belt drive XP2 over dimensioned Compressor cooling system Air/Oil Oil cooling capacity 5 litres / 1.33 gallons Air outlet temperature 20C + Ambient temperature Hose Diameter 3/4" Outlet connector Claw Noise level EECno 2000/14 <98 LWA Battery 12Vcc 300A-30Ah (EN) 2

Fuel tank capacity 15L / 4 gallons Weight 240K

### Please see the specification sheet for further details