

Martindale NC4 Dual Sensitivity Non-Contact Voltage Tester

Product Images

Product Code: C70-7320



Short Description

The NC4 voltage tester has two sensitivity ranges for accurately detecting the presence of AC voltages.

The first will detect voltages between 50V and 1000V and the second will indicate voltages between 12V and 1000V. Sensitivity can be set according to the application and when in high sensitivity mode the LED pulse double flashes.

The extended probe tip gives improved access and easier identification of live wiring. It indicates voltage by illuminating the clear tip section with a bright red LED and sounding a buzzer.

The pen-shaped design with clip makes it ideal for carrying in a pocket or tool belt when working at height or in difficult to access locations. There is a useful LED torch which illuminates the area directly in front of the tip. Auto power off and a recessed on button ensure a long battery lifetime and the NC4 functionality also includes low battery indication.

Specifications

Indication Ranges

Default: 50-1000V AC

High sensitivity: 12-1000V AC
40-400Hz

Indication Audible and LED

Conforms to BS EN 61010-1

Supply 2x AAA batteries (included)

Weight 55g (incl. battery)

Dimensions 155mm length, approx. 25mm diameter

Description

The NC4 voltage tester has two sensitivity ranges for accurately detecting the presence of AC voltages. The first will detect voltages between 50V and 1000V and the second will indicate voltages between 12V and 1000V. Sensitivity can be set according to the application and when in high sensitivity mode the LED pulse double flashes.

The extended probe tip gives improved access and easier identification of live wiring. It indicates voltage by illuminating the clear tip section with a bright red LED and sounding a buzzer.

The pen-shaped design with clip makes it ideal for carrying in a pocket or tool belt when working at height or in difficult to access locations. There is a useful LED torch which illuminates the area directly in front of the tip. Auto power off and a recessed on button ensure a long battery lifetime and the NC4 functionality also includes low battery indication.

Specifications

Indication Ranges

Default: 50-1000V AC

High sensitivity: 12-1000V AC

40-400Hz

Indication Audible and LED
Conforms to BS EN 61010-1
Supply 2x AAA batteries (included)
Weight 55g (incl. battery)
Dimensions 155mm length, approx. 25mm diameter