

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

Bicotest TruPol True Polarity Tester for PME Systems

Product Images Product Code: C00-0160





Short Description

The Bicotest TruPol is primarily designed for electricity distribution companies to indicate crosspolarities

of the incoming customer supply.

To ensure that there is not a possibility of an incorrect interpretation of the indication, the usermust positively press the test button to give a ground reference before a test is conducted, eliminating user error whist conducting the test - this is a unique feature of the TruPol.

It is used to test the total supply system polarity and indicate a reversed Live/Neutral on a PMEsystem very quickly, effectively & safely, highlighting the issue not easily detectable using othermeans.

This modern and durable piece of test equipment can also be used as plug tester indicating upto 19 possible wiring conditions. Indication is given both visually and audibly with a strongwarbling tone for any fault, and a continuous tone for good wiring.

Features

Clear indication if there is DNO Cross Polarity Visual and audible feedback Indication of up to 19 different wiring conditions Logical & simple `Green for Go`LED Indication

Specifications

Voltage Rating: 230V @ 50Hz

Input current: <15mA

Temperature / humidity: 0-40°C / 95% non condensing

Safety: BSEN 61010-1

Duty cycle: Non continuous, <2 min.

Description

The Bicotest TruPol is primarily designed for electricity distribution companies to indicate crosspolarities of the incoming customer supply.

To ensure that there is not a possibility of an incorrect interpretation of the indication, the usermust positively press the test button to give a ground reference before a test is conducted, eliminating user error whist conducting the test - this is a unique feature of the TruPol.

It is used to test the total supply system polarity and indicate a reversed Live/Neutral on a PMEsystem very quickly, effectively & safely, highlighting the issue not easily detectable using other means.

This modern and durable piece of test equipment can also be used as plug tester indicating upto 19 possible wiring conditions. Indication is given both visually and audibly with a strong warbling tone for any fault, and a continuous tone for good wiring.

Features

Visual and audible feedback Indication of up to 19 different wiring conditions Logical & simple `Green for Go`LED Indication

Specifications

Voltage Rating: 230V @ 50Hz

Input current: <15mA

Temperature / humidity: 0-40°C / 95% non condensing

Safety: BSEN 61010-1

Duty cycle: Non continuous, <2 min.