

Megger VF5 Voltstick

Product Images

Product Code: C72-2516



Short Description

The Megger VF5 Voltage Detector is intended to be used to check for the presence of AC voltage, indicated by a bright red LED situated within the white nylon tip, an audible sounder, plus vibration alert.

The detector has both low voltage (12 - 1000 V) and medium voltage (100 - 1000 V) ranges.

The VF5 has the added advantage of a bright-white LED torch for use in poor light.

Features

AC non-contact voltage detector

12V – 1000V voltage range

„Visual, audible and vibration warning of low and medium voltages

„Durable rubber over-moulded body

„IP67 rated

„Screw-on battery cover

„Built-in bright-white LED torch

„CAT IV 1000V

Application

Suitable for identifying live conductors, finding a break in a conductor or verifying a blown fuse while in circuit and detecting AC voltage at socket outlets, switches, circuit breakers, fuses, cables and luminaires.

Specifications

Detection voltage range 12 V AC to 1000 V AC, 100 V to 1000 V AC

Frequency range 50/60 Hz

Batteries 2 x AAA / LR03 1.5 V batteries

Ambient Operating temperature 32 °F to 122 °F (0 °C to 50 °C)

Storage temperature 14 °F to 140 °F (-10 °C to 60 °C)

Humidity 80 % max

Altitude 2000 metres

Pollution Degree 2

Safety Compliance CAT IV 1000 V

Auto Power Off 5 minutes

IP Rating IP67

Description

The Megger VF5 Voltage Detector is intended to be used to check for the presence of AC voltage, indicated by a bright red LED situated within the white nylon tip, an audible sounder, plus vibration

alert.

The detector has both low voltage (12 - 1000 V) and medium voltage (100 - 1000 V) ranges.

The VF5 has the added advantage of a bright-white LED torch for use in poor light.

Features

AC non-contact voltage detector

12V – 1000V voltage range

„Visual, audible and vibration warning of low and medium voltages

„Durable rubber over-moulded body

„IP67 rated

„Screw-on battery cover

„Built-in bright-white LED torch

„CAT IV 1000V

Application

Suitable for identifying live conductors, finding a break in a conductor or verifying a blown fuse while in circuit and detecting AC voltage at socket outlets, switches, circuit breakers, fuses, cables and luminaires.

Specifications

Detection voltage range 12 V AC to 1000 V AC, 100 V to 1000 V AC

Frequency range 50/60 Hz

Batteries 2 x AAA / LR03 1.5 V batteries

Ambient Operating temperature 32 °F to 122 °F (0 °C to 50 °C)

Storage temperature 14 °F to 140 °F (-10 °C to 60 °C)

Humidity 80 % max

Altitude 2000 metres

Pollution Degree 2

Safety Compliance CAT IV 1000 V

Auto Power Off 5 minutes

IP Rating IP67