

Regin Gas & Water Jointing Compound 250g

Product Images

Product Code: R99-0504



Short Description

Regin REGM20 Gas & Water Jointing Compound 250g

Features

- Soft Setting.
- Non-toxic. 250g tub.
- Soft setting non-petroleum based thread sealant for use with potable water and mains gas.
- WRAS Approved for use on cold potable water systems.
- Suitable for Registered Gas Installations.
- Suitable for use on gas installation pipe-work as a class A, Arp and class B thread sealant as defined by BS751-2:1997.
- Easily applied and brushable.
- Working temperature -45°C to +260° C.
- Maximum working pressure: 10,000 psi (liquids) 2,000 psi (gases).
- Can be used on steel, aluminium, brass, copper, polythene, reinforced fibreglass and PVC.
- Not suitable for use with ABS.
- Not suitable for transportation systems containing oxygen, powerful oxidants, concentrated acids or alkalis.

Description

Regin REGM20 Gas & Water Jointing Compound 250g

Features

Soft Setting.

Non-toxic. 250g tub.

Soft setting non-petroleum based thread sealant for use with potable water and mains gas.

WRAS Approved for use on cold potable water systems.

Suitable for Registered Gas Installations.

Suitable for use on gas installation pipe-work as a class A, Arp and class B thread sealant as defined by BS751-2:1997.

Easily applied and brushable.

Working temperature -45°C to +260° C.

Maximum working pressure: 10,000 psi (liquids) 2,000 psi (gases).

Can be used on steel, aluminium, brass, copper, polythene, reinforced fibreglass and PVC.

Not suitable for use with ABS.

Not suitable for transportation systems containing oxygen, powerful oxidants, concentrated acids or alkalis.