

Metrel MI 3109PRO EurotestPV Lite Pro Kit

Product Images

Product Code: C70-2037



Short Description

The Metrel MI 3109 EurotestPV Lite is a photovoltaic (PV) tester that performs all necessary tests

required on photovoltaic installations. This includes all of the tests as required by EN 62446, but also includes I - U characteristic measurements, calculation of STC values and power measurements on Inverter's DC and AC sides (single-phase only).

The MI 3109 EurotestPV Lite is optimized for PV tests therefore the Autotest operation mode is implemented which is intended to perform a complete set of tests needed for verification of PV installations according to EN 62446 with the pressing of only one button.

With this instrument, the tests for the first inspection of PV systems as well as periodic maintenance tests, evaluation tests or troubleshooting tests are possible.

Features

Insulation and I-U curve measurements in one instrument: with MI 3109 only one instrument is needed to perform insulation measurements with up to 1000V for proofing the PV installation safety and I-U curve measurements needed for evaluation and troubleshooting of PV modules or strings.

Autotest: This function is intended to perform a complete set of tests according to EN 62446 on PV modules or strings with pressing only one button:

- insulation resistance between positive output and earth;
- insulation resistance between negative output and earth;
- open circuit voltage;
- short circuit current.

Calculation to STC values: the measured current and voltage values are, according to environment conditions, recalculated to Standard Test Condition values which makes possible to compare the results of different measurements even if they were taken under different test conditions.

Efficiency calculations: 2 voltage & 2 current channels for simultaneous AC & DC parameters measurements.

PV Remote Unit: Optional unit for simultaneous measurements of solar irradiation and temperature of PV module.

Graphical representation of module's I - U curve: the I-V characteristic of PV module or string is graphically represented on LCD display.

Memory: Up to 1800 test results or up to 500 graphical results with timestamp can be stored in internal memory.

BT connectivity: it enables BT communication with Android tablets and smart phones via optional BT dongle.

Android application: enables advanced data management APP EuroLink PV.

Downloadable: PC SW EuroLink PRO enables downloading, review, analyses and printing of test results.

Measuring Functions

PV Installations

Measurements on DC side of PV installation:

Insulation resistance;

Continuity of PE conductors;

Uoc (Open Circuit Voltage) and Isc (Short Circuit Current);

I - U curve of PV modules and strings;

Voltage, current and power of strings and inverters;

Irradiance;

Module temperature.

2

Measurements on AC side of PV installation:
Voltage, current, power;
Efficiency of PV module, inverter, PV system calculation.

Electrical installations

Insulation resistance;
Continuity of PE conductors;
Line impedance;
Loop impedance (sub-functions with high current and without RCD tripping);
RCD testing (type AC, A and B);
Earth resistance;
AC current (load and leakage);
TRMS voltage, frequency, phase sequence;
Power, energy, harmonics.

Contents

- Instrument MI 3109 EurotestPV Lite
- EurotestPV Remote
- PV Safety Probe
- Pyranometer
- Temperature probe
- Soft carrying bag, 2 pcs
- Universal PV test lead, 3 x 1.5 m
- PV Continuity test lead, 2 x 1,5 m
- Test probe, 3 pcs (red, blue, green)
- Crocodile clip, 3 pcs (red, blue, green)
- PV MC3/4 male/female adapters
- AC/DC current clamp
- Power supply adapter + 6 NiMH batteries, type AA
- USB and RS232 - PS/2 cable
- PC SW EuroLink PRO
- Carrying strap
- Short instruction manual
- Instruction manual and handbook on CD
- Calibration certificate

Description

The Metrel MI 3109 EurotestPV Lite is a photovoltaic (PV) tester that performs all necessary tests required on photovoltaic installations. This includes all of the tests as required by EN 62446, but also includes I - U characteristic measurements, calculation of STC values and power measurements on Inverter's DC and AC sides (single-phase only).

The MI 3109 EurotestPV Lite is optimised for PV tests therefore the Autotest operation mode is

implemented which is intended to perform a complete set of tests needed for verification of PV installations according to EN 62446 with the pressing of only one button.

With this instrument, the tests for the first inspection of PV systems as well as periodic maintenance tests, evaluation tests or troubleshooting tests are possible.

Features

Insulation and I-U curve measurements in one instrument: with MI 3109 only one instrument is needed to perform insulation measurements with up to 1000V for proofing the PV installation safety and I-U curve measurements needed for evaluation and troubleshooting of PV modules or strings.

Autotest: This function is intended to perform a complete set of tests according to EN 62446 on PV modules or strings with pressing only one button:

- insulation resistance between positive output and earth;
- insulation resistance between negative output and earth;
- open circuit voltage;
- short circuit current.

Calculation to STC values: the measured current and voltage values are, according to environment conditions, recalculated to Standard Test Condition values which makes possible to compare the results of different measurements even if they were taken under different test conditions.

Efficiency calculations: 2 voltage & 2 current channels for simultaneous AC & DC parameters measurements.

PV Remote Unit: Optional unit for simultaneous measurements of solar irradiation and temperature of PV module.

Graphical representation of module's I - U curve: the I-V characteristic of PV module or string is graphically represented on LCD display.

Memory: Up to 1800 test results or up to 500 graphical results with timestamp can be stored in internal memory.

BT connectivity: it enables BT communication with Android tablets and smart phones via optional BT dongle.

Android application: enables advanced data management APP EuroLink PV.

Downloadable: PC SW EuroLink PRO enables downloading, review, analyses and printing of test results.

Measuring Functions

PV Installations

Measurements on DC side of PV installation:

Insulation resistance;

Continuity of PE conductors;

Uoc (Open Circuit Voltage) and Isc (Short Circuit Current);

I - U curve of PV modules and strings;

Voltage, current and power of strings and inverters;

Irradiance;

Module temperature.

Measurements on AC side of PV installation:

Voltage, current, power;

Efficiency of PV module, inverter, PV system calculation.

Electrical installations

Insulation resistance;
Continuity of PE conductors;
Line impedance;
Loop impedance (sub-functions with high current and without RCD tripping);
RCD testing (type AC, A and B);
Earth resistance;
AC current (load and leakage);
TRMS voltage, frequency, phase sequence;
Power, energy, harmonics.

Contents

Instrument MI 3109 EurotestPV Lite
EurotestPV Remote
PV Safety Probe
Pyranometer
Temperature probe
Soft carrying bag, 2 pcs
Universal PV test lead, 3 x 1.5 m
PV Continuity test lead, 2 x 1,5 m
Test probe, 3 pcs (red, blue, green)
Crocodile clip, 3 pcs (red, blue, green)
PV MC3/4 male/female adapters
AC/DC current clamp
Power supply adapter + 6 NiMH batteries, type AA
USB and RS232 - PS/2 cable
PC SW EuroLink PRO
Carrying strap
Short instruction manual
Instruction manual and handbook on CD
Calibration certificate