

Low Profile Head UV-Resistant Cable Tie 260 x 9mm Pk100

Product Images

Product Code: R02-1957



Short Description

Robust cable ties manufactured from PA11 have many technical features making them suitable for use

in a variety of applications to fix and support cables, pipes and other elements.

They offer an excellent resistance to chemicals in most challenging environments like offshore or on oil rigs and construction vehicles.

In addition, the very good UV resistance makes them a perfect choice for solar panel installations.

Features

Made of Polyamide 11, a sustainable bioplastic
Outside serrated cable tie with rounded head design
Low insertion force for tool-free application
High tensile strength with a single – or a double-bridged head
Soft material for easy handling without damaging the bundle
Very good UV resistance and durability in outdoor applications
Stable technical performance even at very low temperatures
Offers limited resistance to acids, bases and oxidising agents
Low water absorption rate and high durability
Prelocking possible by pushing the strap through the eyelet

Specifications

ELV compliant Dir. Art. 4 (2) YES
Flammability UL 94 HB
Hazardous good No
Operating Temperature - °C -40 °C to +85 °C

Pack size 100

HellermannTyton Art.-No. 112-00012 | (LPH962)-PA11-BK

Description

Robust cable ties manufactured from PA11 have many technical features making them suitable for use in a variety of applications to fix and support cables, pipes and other elements.

They offer an excellent resistance to chemicals in most challenging environments like offshore or on oil rigs and construction vehicles.

In addition, the very good UV resistance makes them a perfect choice for solar panel installations.

Features

Made of Polyamide 11, a sustainable bioplastic
Outside serrated cable tie with rounded head design
Low insertion force for tool-free application
High tensile strength with a single – or a double-bridged head
Soft material for easy handling without damaging the bundle

Very good UV resistance and durability in outdoor applications
Stable technical performance even at very low temperatures
Offers limited resistance to acids, bases and oxidising agents
Low water absorption rate and high durability
Prelocking possible by pushing the strap through the eyelet

Specifications

ELV compliant Dir. Art. 4 (2) YES
Flammability UL 94 HB
Hazardous good No
Operating Temperature - °C -40 °C to +85 °C

Pack size 100

HellermannTyton Art.-No. 112-00012 | (LPH962)-PA11-BK