

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Torque Mount 35 8x19 mm High Impact Modified UV-Resistant Pk100

Product Images

Product Code: R02-1956



These heavy duty mounts (HDM) can be found in a variety of applications requiring heavy duty mounting in areas like the solar, railway, defence and/or agriculture industry.

Features

Design offers secure alignment to the bundle Possible replacement of cushion clamps and/or metal clamps Eliminates the needs for multiple sized fix diameter clamps For heavy duty cable ties up to 12.7 mm width High tightening torque through metal bushing Easy maintenance of bundle by simply changing the cable tie

Fixation Method Screw Mounting and Rivet Material Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) Mounting Screw Type #1/4" (M6) Screw

ELV compliant Dir. Art. 4 (2) YES Flammability UL 94 HB Halogenfree Yes Max. Torque (kgf-cm) 132.5kgf-cm Max. Torque (lbf-ln) 9.583lbf-ft Operating Temperature - °C -40 °C to +105 °C, (+105 °C for 500 h)

HellermannTyton Art.-No. 151-00437 | HDM25-PA66HIRHSUV-BK

Description

These heavy duty mounts (HDM) can be found in a variety of applications requiring heavy duty mounting in areas like the solar, railway, defence and/or agriculture industry.

<u>Features</u>

Design offers secure alignment to the bundle Possible replacement of cushion clamps and/or metal clamps Eliminates the needs for multiple sized fix diameter clamps For heavy duty cable ties up to 12.7 mm width High tightening torque through metal bushing Easy maintenance of bundle by simply changing the cable tie

Fixation Method Screw Mounting and Rivet Material Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) Mounting Screw Type #1/4" (M6) Screw

https://www.millsltd.com/default/torque-mount-35-8x19-mm-high-impact-modified-uv-resistant-pk100.html 20/04/2024

Specifications

ELV compliant Dir. Art. 4 (2) YES Flammability UL 94 HB Halogenfree Yes Max. Torque (kgf-cm) 132.5kgf-cm Max. Torque (lbf-ln) 9.583lbf-ft Operating Temperature - °C -40 °C to +105 °C, (+105 °C for 500 h)

HellermannTyton Art.-No. 151-00437 | HDM25-PA66HIRHSUV-BK