

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Rodent Resistant Dark Brown Cable Braid 3/8" - 37.5m Roll

Product Images Product Code: R02-0066







Short Description

Rodent Resistant 3/8" Dark Brown Flexo Rodent Resistant (RRN) is the latest solution from Techflex for

fighting the harmful effects of unprotected wires which are exposed to rodents.

Mice, rats and other rodents have never ending time to find and destroy wiring and hose systems. Techflex has once again combined our knowledge of technical filaments and braided protection sleeves to create an amazing rodent resistant sleeving.

Supplied on a 37.5 metre roll.

Specifications

Expansion Max: 12.7mm (1/2")

Expansion Min: 4.7mm (3/16")

PHYSICAL PROPERTIES

Monofilament Diameter: 0.25 mm Recommended Cutting: Hot Knife

Colors: 1

Wall Thickness: 0.64 mm Tensile Strength: 7.5 Abrasion Resistance: Low Specific Gravity: 1.38

Moisture Absorption Percent (%): 0.1 - 0.2

HARD VACCUUM DATA

TML: .19 CVCM: .00 WVR: .16

Smoke D-Max: 56 Outgassing: Medium Oxygen Index: 21

OPERATING TEMPERATURES

Minimum Continuous: -94 °F / -70 °C Maximum Continuous: 257 °F / 125 °C

Melt: 482 °F / 250 °C

CHEMICAL RESISTANCE

1 = No Effect, 2 = Little Effect, 3 = Affected, 4 = More Affected, 5 = Severely Affected

Aromatic Solvents: 2 Aliphatic Solvents: 1 Chlorinated Solvents: 3

Weak Bases: 1

Salts: 1

Strong Bases: 2
Salt Water: 1
Hydraulic Fluid: 1
Lube Oil: 1
De-Icing Fluid: 1

Strong Acids: 3

Strong Oxidants: 2 Esters / Ketones: 1

UV Light: 1 Petroleum: 1 Fungus: 1

OTHER INFORMATION Halogen Free: Yes

ROHS: Yes SVHC: None UL: No

*Please use caution while handling Flexo Rodent Resistant. May cause skin and/or eye irritation.

*Please Note: The RRN is a Preventive but not guaranteed to stop rodents from causing damage.

Ref RRN0.38D

Description

Rodent Resistant 3/8" Dark Brown Flexo Rodent Resistant (RRN) is the latest solution from Techflex for fighting the harmful effects of unprotected wires which are exposed to rodents.

Mice, rats and other rodents have never ending time to find and destroy wiring and hose systems. Techflex has once again combined our knowledge of technical filaments and braided protection sleeves to create an amazing rodent resistant sleeving.

Supplied on a 37.5 metre roll.

Specifications

Expansion Max: 12.7mm (1/2")

Expansion Min: 4.7mm (3/16")

PHYSICAL PROPERTIES

Monofilament Diameter: 0.25 mm Recommended Cutting: Hot Knife

Colors: 1

Wall Thickness: 0.64 mm Tensile Strength: 7.5 Abrasion Resistance: Low Specific Gravity: 1.38

Moisture Absorption Percent (%): 0.1 - 0.2

HARD VACCUUM DATA

TML: .19

WVR: .16

Smoke D-Max: 56 Outgassing: Medium Oxygen Index: 21

OPERATING TEMPERATURES

Minimum Continuous: -94 °F / -70 °C Maximum Continuous: 257 °F / 125 °C

Melt: 482 °F / 250 °C

CHEMICAL RESISTANCE

1 = No Effect, 2 = Little Effect, 3 = Affected, 4 = More Affected, 5 = Severely Affected

Aromatic Solvents: 2 Aliphatic Solvents: 1 Chlorinated Solvents: 3

Weak Bases: 1

Salts: 1

Strong Bases: 2 Salt Water: 1 Hydraulic Fluid: 1

Lube Oil: 1

De-Icing Fluid: 1 Strong Acids: 3 Strong Oxidants: 2 Esters / Ketones: 1

UV Light: 1 Petroleum: 1 Fungus: 1

OTHER INFORMATION

Halogen Free: Yes

ROHS: Yes SVHC: None UL: No

*Please use caution while handling Flexo Rodent Resistant. May cause skin and/or eye irritation.

*Please Note: The RRN is a Preventive but not guaranteed to stop rodents from causing damage.

Ref RRN0.38D