

RidgeGear RGHK12 Twin Leg BigGuy Kit - XL

Product Images

Product Code: S00-0666



Short Description

This BigGuy kit comes complete with a two point safety harness and a twin leg fall arrest safety lanyard.

The lanyard is suitable for a user weight of up to 140kg.

The combination allows work to take place at an open edge or ungated ladder hatch.

This version comes with two ANSI approved scaffold hooks meaning it is ideal for clipping to scaffolding or other steel structures.

The twin leg feature allows operatives to move between fixed anchor points through means of double clipping.

Accredited to: EN 361:2002, EN 355:2002

Kit Contains: RGH2 Big Guy front and rear D harness

RGL3 Big Guy twin leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 2 x attached RGK88 scaffold hooks

RGH2 Big Guy Front and Rear D Harness

Front & Rear D Safety Harness tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards.

This two point safety harness has both a rear and chest mounted front attachment point.

The two attachment points extend this harness's working capability, meaning it can be used for fall protection and restraint situations in either vertical or horizontal planes.

The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring.

High contrast stitching makes inspection easier.

The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment.

Harness design minimises the amount of rigid webbing edges.

Features

Tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards

Front & rear attachment points

Lightweight

Rip stitch fall indicators

Full adjustable (Easy slide shoulder adjusters)

Specifications

Accredited to: EN 361:2002

Web material: 45mm water repellent polyester

Fittings: High tensile steel alloy

Weight: 1.1kg

RidgeGear RGL3 Big Guy Twin Leg Lanyard

Twin Leg Webbing Lanyard & Shock Absorber tested and approved for a user weight up to 140kg.

A twin leg lanyard with the same specifications as the RGL1 BigGuy additionally allows movement between anchorage points by means of double clipping and ensures continuous attachment.

The RGL3 BigGuy is supplied at a length of 1.4m including hooks/karabiners.

This system is generally used for tower climbing, steel erecting, scaffolding and maintenance on open structures.

Recommended for use with RGH2 BigGuy Harness.

Specifications

Accredited to: EN 355:2002

Web material: 26mm water repellent polyester 32kN

Fittings: RGK1 and 2 x RGK88

Max arrest force: <6kN including fall factor 2

Length: 1.4 including connectors

Description

This BigGuy kit comes complete with a two point safety harness and a twin leg fall arrest safety lanyard. The lanyard is suitable for a user weight of up to 140kg.

The combination allows work to take place at an open edge or ungated ladder hatch.

This version comes with two ANSI approved scaffold hooks meaning it is ideal for clipping to scaffolding or other steel structures.

The twin leg feature allows operatives to move between fixed anchor points through means of double clipping.

Accredited to: EN 361:2002, EN 355:2002

Kit Contains: RGH2 Big Guy front and rear D harness

RGL3 Big Guy twin leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 2 x attached RGK88 scaffold hooks

RGH2 Big Guy Front and Rear D Harness

Front & Rear D Safety Harness tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards.

This two point safety harness has both a rear and chest mounted front attachment point.

The two attachment points extend this harness's working capability, meaning it can be used for fall

protection and restraint situations in either vertical or horizontal planes.

The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring.

High contrast stitching makes inspection easier.

The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment.

Harness design minimises the amount of rigid webbing edges.

Features

Tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards
Front & rear attachment points

Lightweight

Rip stitch fall indicators

Full adjustable (Easy slide shoulder adjusters)

Specifications

Accredited to: EN 361:2002

Web material: 45mm water repellent polyester

Fittings: High tensile steel alloy

Weight: 1.1kg

RidgeGear RGL3 Big Guy Twin Leg Lanyard

Twin Leg Webbing Lanyard & Shock Absorber tested and approved for a user weight up to 140kg.

A twin leg lanyard with the same specifications as the RGL1 BigGuy additionally allows movement between anchorage points by means of double clipping and ensures continuous attachment.

The RGL3 BigGuy is supplied at a length of 1.4m including hooks/karabiners.

This system is generally used for tower climbing, steel erecting, scaffolding and maintenance on open structures.

Recommended for use with RGH2 BigGuy Harness.

Specifications

Accredited to: EN 355:2002

Web material: 26mm water repellent polyester 32kN

Fittings: RGK1 and 2 x RGK88

Max arrest force: <6kN including fall factor 2

Length: 1.4 including connectors