

# RidgeGear RGHK11 Single Leg BigGuy Kit - Large

Product Images

Product Code: S00-0663



## Short Description

The RidgeGear BigGuy kit comes complete with a two point safety harness and a single leg fall arrest

safety lanyard.

The lanyard is suitable for a user weight of up to 140kg. The combination allows work to take place at an open edge or un-gated ladder hatch.

The lanyard comes attached with an ANSI approved scaffold hook which has a stronger gate.

The hook is designed for simple connection to scaffolding and other steel structures.

Accredited to: EN 361:2002, EN 355:2002

#### Kit Contents

RGH2 Big Guy front and rear D harness

RGL1 Big Guy single leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 1 x attached RGK88 scaffold hook.

### **RGH2 Big Guy Front and Rear D Harness**

Front & Rear D Safety Harness tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards.

This two point safety harness has both a rear and chest mounted front attachment point.

The two attachment points extend this harness's working capability, meaning it can be used for fall protection and restraint situations in either vertical or horizontal planes.

The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring.

High contrast stitching makes inspection easier.

The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment.

Harness design minimises the amount of rigid webbing edges.

#### Features

Tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards

Front & rear attachment points

Lightweight

Rip stitch fall indicators

Full adjustable (Easy slide shoulder adjusters)

#### Specifications

Accredited to: EN 361:2002

Web material: 45mm water repellent polyester

Fittings: High tensile steel alloy

Weight: 1.1kg

## RidgeGear RGL1 Big Guy Single Leg Lanyard

Single Leg Webbing Lanyard & Shock Absorber tested and approved for a user weight up to 140kg.

The RGL1 BigGuy is supplied with a length of 1.4m including hooks/karabiners.

An industry standard, and usually the minimum equipment issued/required with a harness for anyone working at height.

37 kN polyester webbing is used to manufacture the lanyard which helps give the product exceptional strength and a longer life. It is also treated with a water repellent coating which also extends the life of this product.

Recommended for use with RGH2 BigGuy Harness.

### Specifications

Accredited to: EN 355:2002

Web material: 26mm water repellent polyester

Fittings: RGK1 & RGK88

Max arrest force: <6kN including fall factor 2

Length: 1.4m including connectors

## Description

---

The RidgeGear BigGuy kit comes complete with a two point safety harness and a single leg fall arrest safety lanyard.

The lanyard is suitable for a user weight of up to 140kg. The combination allows work to take place at an open edge or un-gated ladder hatch.

The lanyard comes attached with an ANSI approved scaffold hook which has a stronger gate.

The hook is designed for simple connection to scaffolding and other steel structures.

Accredited to: EN 361:2002, EN 355:2002

### Kit Contents

RGH2 Big Guy front and rear D harness

RGL1 Big Guy single leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 1 x attached RGK88 scaffold hook.

## RGH2 Big Guy Front and Rear D Harness

Front & Rear D Safety Harness tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards.

This two point safety harness has both a rear and chest mounted front attachment point.

The two attachment points extend this harness's working capability, meaning it can be used for fall protection and restraint situations in either vertical or horizontal planes.

The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring.

High contrast stitching makes inspection easier.

The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment.

Harness design minimises the amount of rigid webbing edges.

### Features

Tested and approved for a user weight up to 140kg, when used in conjunction with the BigGuy Lanyards

Front & rear attachment points

Lightweight

Rip stitch fall indicators

Full adjustable (Easy slide shoulder adjusters)

### Specifications

Accredited to: EN 361:2002

Web material: 45mm water repellent polyester

Fittings: High tensile steel alloy

Weight: 1.1kg

## **RidgeGear RGL1 Big Guy Single Leg Lanyard**

Single Leg Webbing Lanyard & Shock Absorber tested and approved for a user weight up to 140kg.

The RGL1 BigGuy is supplied with a length of 1.4m including hooks/karabiners.

An industry standard, and usually the minimum equipment issued/required with a harness for anyone working at height.

37 kN polyester webbing is used to manufacture the lanyard which helps give the product exceptional strength and a longer life. It is also treated with a water repellent coating which also extends the life of this product.

Recommended for use with RGH2 BigGuy Harness.

### Specifications

Accredited to: EN 355:2002

Web material: 26mm water repellent polyester

Fittings: RGK1 & RGK88

Max arrest force: <6kN including fall factor 2

Length: 1.4m including connectors