

Heightec L2T150S Elite Twin Lanyard – Tri-Act Scaff Hook 1.5m

Product Images

Product Code: S83-1091



Short Description

Twin lanyard with triple action karabiner, scaffold hooks and energy absorber with built-in suspension

intolerance relief footloop

ELITE twin lanyard – tri-act for fall arrest of the very highest specification. The heightec ELITE twin lanyard – tri-act is a premium product offering advanced safety features.

Allows continuous connection to a ladder or structure when climbing masts and towers. With tri-act and scaffold hook terminations.

Integral suspension intolerance relief footloop. Deploys automatically providing support for both feet. heightec ELITE lanyards are the only lanyards on the market with an automatically deploying footloop.

Heatshrunken absorber with replacement cover, tamper evident but with increased durability. Replacement absorber covers available to purchase separately.

Absorber will not deploy at force less than 200 kg. Minimum strength 1500 kg after deployment.

Patented HELIX™ ropes allow high degree of twist in lanyard legs minimising kinking which occurs with normal kernmantel rope versions.

Large central ring provides parking point for unused leg and prevents issues caused by 3 way loading.

Unique serial ID number allows easy management of equipment.

Approved for users up to 140 kg.

Sewn terminations with high strength 22 kN Scaffold hooks.

Every lanyard is individually numbered. heightec do not recommend attaching lanyards to harnesses with standard oval or offset D karabiners.

Lengths available: 1.25 m, 1.5 m, 1.6 m, 1.75 m

Description

Twin lanyard with triple action karabiner, scaffold hooks and energy absorber with built-in suspension intolerance relief footloop

ELITE twin lanyard – tri-act for fall arrest of the very highest specification. The heightec ELITE twin lanyard – tri-act is a premium product offering advanced safety features.

Allows continuous connection to a ladder or structure when climbing masts and towers. With tri-act and scaffold hook terminations.

Integral suspension intolerance relief footloop. Deploys automatically providing support for both feet. heightec ELITE lanyards are the only lanyards on the market with an automatically deploying footloop.

Heatshrunken absorber with replacement cover, tamper evident but with increased durability. Replacement absorber covers available to purchase separately.

Absorber will not deploy at force less than 200 kg. Minimum strength 1500 kg after deployment.

Patented HELIX™ ropes allow high degree of twist in lanyard legs minimising kinking which occurs with normal kernmantel rope versions.

Large central ring provides parking point for unused leg and prevents issues caused by 3 way loading.

Unique serial ID number allows easy management of equipment.

Approved for users up to 140 kg.

Sewn terminations with high strength 22 kN Scaffold hooks.

Every lanyard is individually numbered. heightec do not recommend attaching lanyards to harnesses with standard oval or offset D karabiners.

Lengths available: 1.25 m, 1.5 m, 1.6 m, 1.75 m