

Heightec LA05H Piranha Adjustable Lanyard with Safety Hook & Screwlink 5m

Product Images

Product Code: S83-1096



Short Description

Adjustable lanyard for work positioning on masts, towers, pylons and ladders.

PIRANHA adjustable lanyard with safety hook connector is a compact device used for work positioning on masts, towers, pylons or other lattice structures in the telecoms, power and entertainment industries.

The Piranha adjustable lanyard has a gradual action and can be accurately controlled with one hand – for both taking in and paying out.

Heightec's PIRANHA adjustable lanyard with safety hook allows for precise positioning during the work task.

The sleeve protects the rope against abrasion, sharp edges and contamination.

Use of screwlinks (certain models) helps eliminate risk of side or cross loads, and can be a semi-permanent attachment if required. Adhesive heat shrink prevents the ID label from being damaged or lost.

Replacement ropes are available for the PIRANHA's and can be fitted by the user in minutes and requires only a screwdriver. User can always maintain a grip of the structure for support when adjusting. When used for positioning an additional fall protection system should be used. Meets the requirements of EN795 type B.

NB: When used for positioning an additional fall protection system should be used. Always place equipment so as to minimise a potential fall.

Lengths available: 2m, 3m, 5m.

Description

Adjustable lanyard for work positioning on masts, towers, pylons and ladders.

PIRANHA adjustable lanyard with safety hook connector is a compact device used for work positioning on masts, towers, pylons or other lattice structures in the telecoms, power and entertainment industries.

The Piranha adjustable lanyard has a gradual action and can be accurately controlled with one hand – for both taking in and paying out.

Heightec's PIRANHA adjustable lanyard with safety hook allows for precise positioning during the work task.

The sleeve protects the rope against abrasion, sharp edges and contamination.

Use of screwlinks (certain models) helps eliminate risk of side or cross loads, and can be a semi-permanent attachment if required. Adhesive heat shrink prevents the ID label from being damaged or lost.

Replacement ropes are available for the PIRANHA's and can be fitted by the user in minutes and requires only a screwdriver. User can always maintain a grip of the structure for support when adjusting. When used for positioning an additional fall protection system should be used. Meets the requirements of EN795 type B.

NB: When used for positioning an additional fall protection system should be used. Always place equipment so as to minimise a potential fall.

Lengths available: 2m, 3m, 5m.