

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

# Heightec H34QL Vortex Quick Connect Wind Turbine Harness -Large

Product Images Product Code: S83-1084







## **Short Description**

Lightweight multi-purpose harness with integrated belt, designed specifically for the renewables industry.

The new lightweight VORTEX wind turbine harness with integrated waist belt is designed for work positioning and fall arrest.

The breathable low profile back panel and padded waist belt provide support and protection while climbing. The padded waist belt is fitted with two side D's for work positioning. The back panel also helps to hold the harness in shape, reducing tangling and aiding orientation.

SafeLock™ quick connect leg, waist and chest buckles make fitting fast and easy. Quick connect buckles also allows the harness to be removed without the need for re-adjustment.

Shoulder buckles allow quick and easy adjustment with one hand making the harness easily adjustable for offshore use. Elastic webbing retainers on strap ends allow slack webbing to be stowed neatly and easily.

Chest rings align the webbing to ensure a good fit giving maximum comfort and security.

The rear attachment point is positioned at the nape of the neck to eliminate discomfort when climbing WTG ladders. This high rear point ensures a more vertical orientation of the casualty when lowering during rescue and reduces risk of interference with the ladder rungs.

The integrated parking points allow lanyards to be stowed when not in use, yet break free in a fall preventing issues from incorrect loading. These are positioned on the shoulder pads to avoid the trip hazard associated with longer lanyards.

The VORTEX wind turbine harness complies with Siemens PPE requirements PRO-13838 Ap1.

#### **Features**

- High rear attachment point
- Integrated work positioning belt with side D's
- Low profile breathable back panel and waist pad
- Plastic wear protection in key areas
- Rapid fitting for emergency evacuation
- Contoured fit for comfort and freedom of movement
- SafeLock™ quick connect leg loop and chest buckles
- Integral lanyard parking points
- High load rating 140 kg

#### Sizes available:

- H34Q VORTEX quick connect, standard Torso 78 106 cm. Waist 80 125 cm. Thigh 65 105 cm
- H34QL VORTEX quick connect, large Torso 90 -120 cm. Waist 95 160 cm. Thigh 65 120 cm

## **Description**

Lightweight multi-purpose harness with integrated belt, designed specifically for the renewables industry.

The new lightweight VORTEX wind turbine harness with integrated waist belt is designed for work positioning and fall arrest.

The breathable low profile back panel and padded waist belt provide support and protection while climbing. The padded waist belt is fitted with two side D's for work positioning. The back panel also helps to hold the harness in shape, reducing tangling and aiding orientation.

SafeLock™ quick connect leg, waist and chest buckles make fitting fast and easy. Quick connect buckles also allows the harness to be removed without the need for re-adjustment.

Shoulder buckles allow quick and easy adjustment with one hand making the harness easily adjustable for offshore use. Elastic webbing retainers on strap ends allow slack webbing to be stowed neatly and easily.

Chest rings align the webbing to ensure a good fit giving maximum comfort and security.

The rear attachment point is positioned at the nape of the neck to eliminate discomfort when climbing WTG ladders. This high rear point ensures a more vertical orientation of the casualty when lowering during rescue and reduces risk of interference with the ladder rungs.

The integrated parking points allow lanyards to be stowed when not in use, yet break free in a fall preventing issues from incorrect loading. These are positioned on the shoulder pads to avoid the trip hazard associated with longer lanyards.

The VORTEX wind turbine harness complies with Siemens PPE requirements PRO-13838 Ap1.

### **Features**

High rear attachment point
Integrated work positioning belt with side D's
Low profile breathable back panel and waist pad
Plastic wear protection in key areas
Rapid fitting for emergency evacuation
Contoured fit for comfort and freedom of movement
SafeLock™ quick connect leg loop and chest buckles
Integral lanyard parking points
High load rating 140 kg

Sizes available:

H34Q VORTEX quick connect, standard – Torso 78 – 106 cm. Waist 80 – 125 cm. Thigh 65 – 105 cm H34QL VORTEX quick connect, large – Torso 90 -120 cm. Waist 95 – 160 cm. Thigh 65 – 120 cm