

RidgeGear RGHK2 Scaffolder's Kit - Standard

Product Images

Product Code: S83-1051



Short Description

The Scaffolder's Kit comes complete with a two point harness and single fall arrest lanyard enabling work to take place at an open edge or ungated ladder hatch.

The lanyard comes attached with a scaffold hook which is designed for simple connection to scaffolding and other steel structures.

Accredited to: EN 361:2002, EN 355:2002

Kit Contains:

RGH2 front and rear D harness, RGL1 1.8m single leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 1 x attached RGK11 scaffold hook.

RidgeGear RGH2 Full Body Harness

The RGH2 Full Body Harness is the workhorse of the industry. The harness is fitted with a Rear D Ring and a chest mounted Front D Ring.

The harness is fully adjustable and is fitted with rip stitch indicators.

The ring connection between the chest & the shoulder straps, ensure no stress loading when force is applied to the Front D Ring.

- Fitted with a Rear D Ring and a chest mounted Front D Ring
- Fully adjustable and is fitted with rip stitch indicators
- EN:361 45mm water repellent polyester

RGL1 1.8m Single Leg Webbing Lanyard

The RGL1 lanyard is an industry standard, and normally the minimum equipment issued with a harness for working at height.

The webbing used in the manufacture provides great strength, wear and shear resistance

It is treated with a water repellent coating

This lanyard should be used when the operative is working from a static position, connected to a fixed anchor point

If movement between anchorages is required, a twin leg lanyard should be used (RGL3), to provide constant protection

In the interests of safety, these items are non-returnable and non-refundable (unless faulty)

Description

The Scaffolder's Kit comes complete with a two point harness and single fall arrest lanyard enabling work to take place at an open edge or ungated ladder hatch.

The lanyard comes attached with a scaffold hook which is designed for simple connection to scaffolding and other steel structures.

Accredited to: EN 361:2002, EN 355:2002

Kit Contains:

RGH2 front and rear D harness, RGL1 1.8m single leg webbing lanyard & shock absorber with 1 x attached RGK1 karabiner and 1 x attached RGK11 scaffold hook.

RidgeGear RGH2 Full Body Harness

The RGH2 Full Body Harness is the workhorse of the industry. The harness is fitted with a Rear D Ring and a chest mounted Front D Ring.

The harness is fully adjustable and is fitted with rip stitch indicators.

The ring connection between the chest & the shoulder straps, ensure no stress loading when force is applied to the Front D Ring.

- Fitted with a Rear D Ring and a chest mounted Front D Ring
- Fully adjustable and is fitted with rip stitch indicators
- EN:361 45mm water repellent polyester

RGL1 1.8m Single Leg Webbing Lanyard

The RGL1 lanyard is an industry standard, and normally the minimum equipment issued with a harness for working at height.

The webbing used in the manufacture provides great strength, wear and shear resistance
It is treated with a water repellent coating

This lanyard should be used when the operative is working from a static position, connected to a fixed anchor point

If movement between anchorages is required, a twin leg lanyard should be used (RGL3), to provide constant protection

In the interests of safety, these items are non-returnable and non-refundable (unless faulty)