

RidgeGear RGH15 Work Positioning Comfort Harness - Large

Product Images

Product Code: S83-1044





Short Description

This work positioning safety harness is perfect for lengthy, hands free tasks, due to its lumbar supporting work positioning belt.

The belt makes up two of the four connection points of this harness, the other two being front and rear attachment points.

This comfortable harness is perfect for operatives who are required to work at height or in exposed areas for prolonged periods of time.

The unique design allows the shoulder straps to follow the user's movement.

The addition of easy to use tail tidies, means excess webbing won't hinder the user during work.

If combined with a twin leg lanyard the safety harness can be used for tower climbing, scaffold work and general steel erecting.

Features

- Front, rear, & side attachment points
- Waist, leg & shoulder support pads
- Rip stitch fall indicators
- Adjustable fast fit buckles on leg and front chest straps
- Tool loops
- Double front waist adjustment
- Rear waist adjuster for repositioning of side D rings
- Tail tidies

Accredited to: EN 361:2002, EN 358:2018

Weight: 2.1kg

Max User Weight: 140kg (when the max. force on the user/anchor is limited to <6kN)

Material: 45mm water repellent polyester

Fittings: High tensile steel adjusters, Aluminium lightweight D rings

Description

This work positioning safety harness is perfect for lengthy, hands free tasks, due to its lumbar supporting work positioning belt.

The belt makes up two of the four connection points of this harness, the other two being front and rear attachment points.

This comfortable harness is perfect for operatives who are required to work at height or in exposed areas for prolonged periods of time.

The unique design allows the shoulder straps to follow the user's movement.

The addition of easy to use tail tidies, means excess webbing won't hinder the user during work.

If combined with a twin leg lanyard the safety harness can be used for tower climbing, scaffold work and general steel erecting.

Features

Front, rear, & side attachment points

Waist, leg & shoulder support pads

Rip stitch fall indicators

Adjustable fast fit buckles on leg and front chest straps

Tool loops

Double front waist adjustment

Rear waist adjuster for repositioning of side D rings

Tail tidies

Accredited to: EN 361:2002, EN 358:2018

Weight: 2.1kg

Max User Weight: 140kg (when the max. force on the user/anchor is limited to <6kN)

Material: 45mm water repellent polyester

Fittings: High tensile steel adjusters, Aluminium lightweight D rings