

# RidgeGear Kermantle Rope 11mm x 10m with fitted K11 Scaffold Hook

Product Images

Product Code: S83-1020



## Short Description

---

The RGRO11 11mm kernmantle rope provides vertical, or near vertical fall protection. It is fitted with a single spliced eye and heat-shrink cover.

It is a static rope that is highly abrasion resistant, low stretch, maximum strength, extremely durable and has a long service life.

This rope is has numerous uses it is suitable for rope access and work positioning. It can also be used for rescue work, guide work, expeditions and caving.

Supplied with a fitted K11 Scaffold Hook.

### Features

- High grade polyamide
- Twisted cores
- Ultra-lightweight at high minimum breaking load
- High-twist mantle braid
- Dirt resistant
- Excellent grip / strength
- High abrasion protection

Diameter: 11mm

Length: 10m

### Specifications

Accredited to: EN 353-2:2002, EN 1891A:1998

Material: Polyamide outer sheath and twisted inner core

Max Arrest Force: <6kN (when used with RGA device to EN353-2)

## **RGK11 60mm Aluminium Double Action Scaffold Hook with Captive Eye**

A double action scaffold hook produced from aluminium which is usually used in conjunction with a fall arrest safety lanyard for quick clipping onto scaffold or steel structures.

### Specifications

Accredited to: EN 362:2004

Weight: 480g

Material: Aluminium

Plating: Anodised

Gate Opening: 60mm

External Length: 248mm

Minimum Breaking Strength: 23kN

Closure Type: Double action

## Description

---

The RGRO11 11mm kernmantle rope provides vertical, or near vertical fall protection. It is fitted with a single spliced eye and heat-shrink cover.

It is a static rope that is highly abrasion resistant, low stretch, maximum strength, extremely durable and has a long service life.

This rope is has numerous uses it is suitable for rope access and work positioning. It can also be used for rescue work, guide work, expeditions and caving.

Supplied with a fitted K11 Scaffold Hook.

### Features

High grade polyamide

Twisted cores

Ultra-lightweight at high minimum breaking load

High-twist mantle braid

Dirt resistant

Excellent grip / strength

High abrasion protection

Diameter: 11mm

Length: 10m

### Specifications

Accredited to: EN 353-2:2002, EN 1891A:1998

Material: Polyamide outer sheath and twisted inner core

Max Arrest Force: <6kN (when used with RGA device to EN353-2)

## **RGK11 60mm Aluminium Double Action Scaffold Hook with Captive Eye**

A double action scaffold hook produced from aluminium which is usually used in conjunction with a fall arrest safety lanyard for quick clipping onto scaffold or steel structures.

## Specifications

Accredited to: EN 362:2004

Weight: 480g

Material: Aluminium

Plating: Anodised

Gate Opening: 60mm

External Length: 248mm

Minimum Breaking Strength: 23kN

Closure Type: Double action