


Ripley Miller CFS-3 3 Hole Fibre Optic Stripper

Product Images

Product Code: E00-0952



Short Description

Three-hole design efficiently removes 1.6 mm to 3 mm fibre jackets & buffers down to the 125 micron

bare fibre in one compact tool

All stripping surfaces are quality manufactured to precise tolerances to ensure clean, smooth strips with every use

Factory-set blade notches require no adjustment & will not scratch or nick the fibre

Compliant thermoplastic elastomer handle grips are ergonomically designed to fit comfortably in either hand, reducing the risk of injury from the repetitive stripping function

Min. Outer Jacket Diameter: 1.6 mm

Max. Outer Jacket Diameter: 3 mm

1st Hole Application 1.6 - 3 mm Jacket → 600 - 900 µm Tight Buffer

2nd Hole Application 600 - 900 µm Tight Buffer → 250 µm Buffer Coating

3rd Hole Application 250 µm Buffer Coating → 125 µm Bare Fibre

Length 165 mm

Weight 119 g

Description

Three-hole design efficiently removes 1.6 mm to 3 mm fibre jackets & buffers down to the 125 micron bare fibre in one compact tool

All stripping surfaces are quality manufactured to precise tolerances to ensure clean, smooth strips with every use

Factory-set blade notches require no adjustment & will not scratch or nick the fibre

Compliant thermoplastic elastomer handle grips are ergonomically designed to fit comfortably in either hand, reducing the risk of injury from the repetitive stripping function

Min. Outer Jacket Diameter: 1.6 mm

Max. Outer Jacket Diameter: 3 mm

1st Hole Application 1.6 - 3 mm Jacket → 600 - 900 µm Tight Buffer

2nd Hole Application 600 - 900 µm Tight Buffer → 250 µm Buffer Coating

3rd Hole Application 250 µm Buffer Coating → 125 µm Bare Fibre

Length 165 mm

Weight 119 g