

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

## UltraCrete Envirobed CD534 High Performance Mortar - 48x 18kg Bags

Product Images Product Code: S00-4036







## **Short Description**

The environmentally friendly alternative to resin-based materials, specifically formulated for the bedding of all access covers. Envirobed® CD534 (formerly HA104) has been HAPAS Approved since 2005 and conforms to CD534. Its superior compressive, tensile and flexural strengths make it ideal for use in heavily trafficked / wheel track locations. It can be open to traffic after just 1 hour.

Workability: 15 minutes Set Time: 30 minutes Depth: 10mm -50mm

53N/mm<sup>2</sup> compressive strength in 3 hours 12N/mm<sup>2</sup> flexural strength in 3 hours 6.10N/mm<sup>2</sup> tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C Approved for use on the London Underground and Overground NBS Source registered for ease of specification
UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

48x 18kg bags

48x 2.5 litre plastic bottles

Please see datasheet for further details

## **Description**

The environmentally friendly alternative to resin-based materials, specifically formulated for the bedding of all access covers. Envirobed® CD534 (formerly HA104) has been HAPAS Approved since 2005 and conforms to CD534. Its superior compressive, tensile and flexural strengths make it ideal for use in heavily trafficked / wheel track locations. It can be open to traffic after just 1 hour.

Workability: 15 minutes Set Time: 30 minutes Depth: 10mm -50mm

53N/mm² compressive strength in 3 hours 12N/mm² flexural strength in 3 hours 6.10N/mm² tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C Approved for use on the London Underground and Overground NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

48x 18kg bags

48x 2.5 litre plastic bottles

Please see datasheet for further details