

# UltraCrete Envirobed CD534 Flowable High Performance Mortar - 48x 18kg Bags

Product Images

Product Code: S00-4037



## Short Description

---

Specifically formulated for utility reinstatements. Envirobed® CD534 Flowable (formerly HA104) provides all the performance of Envirobed® CD534 but is significantly easier to apply. It conforms to CD534 and is also BT LN550 and LN320 compliant. It offers superior compressive, tensile and flexural strengths in 3 hours and can be opened to traffic in 1 hour.

### Features

Workability: 15 minutes

Set Time: 30 minutes

Depth: 10mm – 75mm

44N/mm<sup>2</sup> compressive strength in 3 hours

Combines as a bedding mortar and backfill

9.5N/mm<sup>2</sup> flexural strength in 3 hours

5.5N/mm<sup>2</sup> tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C

Aids lateral stability

NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

48x 18kg bags

48x 2.5 litre bottles

**Please see datasheet for further details**

## Description

---

Specifically formulated for utility reinstatements. Envirobed® CD534 Flowable (formerly HA104) provides all the performance of Envirobed® CD534 but is significantly easier to apply. It conforms to CD534 and is also BT LN550 and LN320 compliant. It offers superior compressive, tensile and flexural strengths in 3 hours and can be opened to traffic in 1 hour.

### Features

Workability: 15 minutes

Set Time: 30 minutes

Depth: 10mm – 75mm

44N/mm<sup>2</sup> compressive strength in 3 hours

Combines as a bedding mortar and backfill

9.5N/mm<sup>2</sup> flexural strength in 3 hours

2

<https://www.millsLtd.com/default/ultracrete-envirobed-cd534-flowable-high-performance-mortar-48x-18kg-bags.html>

24/04/2024

5.5N/mm<sup>2</sup> tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C

Aids lateral stability

NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

48x 18kg bags

48x 2.5 litre bottles

**Please see datasheet for further details**