

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

UltraCrete PY4 Summer Grade CD534 Polyester Resin System - 30x 25kg Buckets

Product Images Product Code: S00-4035



Short Description

PY4 SG **Summer Grade** produces a stiff supporting mortar, and is effective for the rapid installation and reinstatement of manhole covers and frames in heavily trafficked areas. It is highly recommended for ductile ironwork and has been HAPAS approved since 2005. PY4 conforms to HA104/09, has a rapid strength gain and can be opened to traffic in 40 minutes.

Features

Workability: 5 - 10 minutes

Set time: 15 minutes Depth: 5mm – 50mm

8.25N/mm² tensile strength in 1 hour

61.5N/mm² compressive strength in 1 hour

19N/mm² flexural strength in 1 hour

NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

30x 25kg buckets

Please see datasheet for further details

Description

PY4 SG **Summer Grade** produces a stiff supporting mortar, and is effective for the rapid installation and reinstatement of manhole covers and frames in heavily trafficked areas. It is highly recommended for ductile ironwork and has been HAPAS approved since 2005. PY4 conforms to HA104/09, has a rapid strength gain and can be opened to traffic in 40 minutes.

Features

Workability: 5 – 10 minutes

Set time: 15 minutes Depth: 5mm – 50mm

8.25N/mm² tensile strength in 1 hour

61.5N/mm² compressive strength in 1 hour

19N/mm² flexural strength in 1 hour

NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

30x 25kg buckets

Please see datasheet for further details